TECHNISCHE SPEZIFIKATION

Powercap® Active™ IP 8 Std. Multinationaler-Stecker

Schwarz / CAE602-941-100



BESCHREIBUNG

PowerCap® Active™ IP ist ein leichter Gebläseatemschutz mit Augen- & Gesichtsaufprallschutz sowie Stoßschutz gemäß EN 812 . PowerCap® Active™ IP ist leicht, fest anliegend, ergonomisch geformt und wurde entwickelt, um den Benutzer vor Staub und den meisten Partikelschadstoffen in der Luft nach EN 12941 TH1P zu schützen.

- 1mm dickes Polycarbonat-Visier mit Aluminiumkanten, die Aufprallschutz bieten - mit Nieten befestigt.

OPTIONEN

Schwarz (CAE602-941-100)

SICHERHEITSSTANDARDS

EN 12941 • EN 812 • EN 166

JSP Limited. Worsham Mill. Minster Lovell. Oxford OX29 0TA. England.

Tel: +44 (0)1993 826050 / Fax: +44 (0)1993 824411 / Email: sales@jspsafety.com / Web: www.jspsafety.com

Do Not Publish without written permission from JSP Limited. Contact copyright@jspsafety.com. Information correct in the United Kingdom at date of issue and may be subject to change. Any third-party machine and automated translations processed by users may have inaccuracies and should not be relied upon.

SPEZIFIKATIONEN

Schirm
7cm

Seitliche Schlagfestigkeit
12 Joules

Min. Temperatur
+5°C

Wiederverwendbar
Schale

Belüftung
Ja

Klassifizierung
TH1 (Turbo Haube)

Anwendung
R (Wiederverwendbar)

Filtrationseffizienz
90%

Nominaler Schutzfaktor
10

Maskendesign
Ein angetriebenes Atemschutzgerät zur Luftreinigung mit Turbohaube (lockere Passform)

Latexfrei
Ja

Filter-Lagerzeit
5 jahre

Batterie Typ
Wiederaufladbare Lithium-Ionen 2 x 3,7 V 1,9 Ah

Optische Klasse 1 (Klasse 1 - Hohe Qualität für den regelmäßigen Gebrauch). 2 - Klasse 2 - Mittlere Qualität für gelegentlichen Gebrauch. 3 – Klasse 3 – Niedrige Qualität für außergewöhnlichen Einsatz)
1

Schutz vor Flüssigkeitsspritzern
3

Produktgewicht
659g

Face Fit Testing Required
Nein

Stoßfestigkeit
12 Joules x 4

Max. Temperatur
+40°C

HDPE-Schale
Ja

Schnallenartiges Gurtverstellsystem
Elastic harness with lockable buckle

Reflektierendes CR2
Nein

Filtertyp
P (schützt gegen feste und flüssige Aerosole)

AUSATEMVENTIL
Nein

Gesamte nach Innen gerichtete Leckage (TIL)
10% bei Montage an einer PowerCap® Active™

UK Zugewiesener Schutzfaktor
10

Gesichtsabdichtungs-Typ
Hypoallergenes Material

Metallfreie
Nein

Filtermaterial
Gefaltete Medien

Markenzeichen des Herstellers
JSP Dolch

Mittlere Aufprallenergie widersteht einer 6mm, 0,86g Stahlkugel bei 120 m/s maximaler Schutz für Überbrillen.
B

BSI Kitemark
Ja

Geräuschpegel
68,2dB

EIGENSCHAFTEN



Kopfschutz durch Anstoßkappe

The cap uses JSP HardCap™ A1+ bump cap technology, exceeding the EN 812 standard. The cap cover is easily removable, wipeable and machine washable.

JSP Limited. Worsham Mill. Minster Lovell. Oxford OX29 0TA. England.

Tel: +44 (0)1993 826050 / Fax: +44 (0)1993 824411 / Email: sales@jspsafety.com / Web: www.jspsafety.com

Do Not Publish without written permission from JSP Limited. Contact copyright@jspsafety.com. Information correct in the United Kingdom at date of issue and may be subject to change. Any third-party machine and automated translations processed by users may have inaccuracies and should not be relied upon.



Powered Air

Protection to EN 12941 TH1P provides a cooling, comfortable supply of filtered air at 160 litres per minute, eliminating breathing resistance and visor misting.



Micro USB Charging

PowerCap® Active™ is supplied with a micro USB cable for recharging in as little as 5 hours. The PowerBox™1 battery pack features a built-in fuel gauge, making it easy to check charge level.



Augen- und Gesichtsschutz

The IP version offers eye and face impact protection to EN 166 1 B, ideal for working in environments where there is a danger of flying particles. Schutzvisiere verfügbar.

SERIE

POWERCAP Active

VIDEOS

www.jspgo.com/UI-FH/UI_PowercapActive/UI_PowercapActive

DOWNLOADS

Bilderordner (ZIP)

doc-powercap_active_ip.pdf (PDF)

JSP Limited. Worsham Mill. Minster Lovell. Oxford OX29 0TA. England.

Tel: +44 (0)1993 826050 / Fax: +44 (0)1993 824411 / Email: sales@jspsafety.com / Web: www.jspsafety.com

Do Not Publish without written permission from JSP Limited. Contact copyright@jspsafety.com. Information correct in the United Kingdom at date of issue and may be subject to change. Any third-party machine and automated translations processed by users may have inaccuracies and should not be relied upon.