

Replacement Jetstream® Dust Filter TH2P R SL

Jetstream® Dust Filter TH2PSL / CBU610-000-000



DESCRIPTION

Replacement TH2P R SL filter for Jetstream® PSL Kits .

*Replacement Jetstream® Dust Filter TH2P R SL meets the requirements of EN 12941 when fitted to Jetstream® respirator.

OPTIONS

Jetstream® Dust Filter TH2PSL (CBU610-000-000)

SAFETY STANDARDS

EN 12941



JSP Limited. Worsham Mill. Minster Lovell. Oxford OX29 0TA. England.

Tel: +44 (0)1993 826050 / Fax: +44 (0)1993 824411 / Email: sales@jspsafety.com / Web: www.jspsafety.com

Do Not Publish without written permission from JSP Limited. Contact copyright@jspsafety.com. Information correct in the United Kingdom at date of issue and may be subject to change. Any third-party machine and automated translations processed by users may have inaccuracies and should not be relied upon.



SPECIFICATIONS

No

Classification TH2 (Turbo Hood)

Usage R (Reusable)



Activated Carbon Layer

Maximum Total Inward Leakage (TIL) 2% When Fitted To Jetstream

UK Assigned Protection Factor 20 When Fitted To A JetStream PSL Unit

Filter Material Pleated Media

Filter Shelf Life 5 Years



Product Weight 124g

RANGE

Jetstream[®] ACCESSORIES

 ∇

Filter Type P (Protects Agaist Solid and Liquid Aerosols)



(D) Resistance to dust clogging Yes - Mandatory Test In EN12491

Minimum Filtration Efficiency 98% For TH2P Rated

Nominal Protection Factor 50 When Fitted to JetStream PSL Unit

Metal Free Yes

Filter Casing Material Polypropylene



BSI Kitemark Yes

DOWNLOADS

Image Pack (ZIP)

doc-jetstream.pdf (PDF)



JSP Limited. Worsham Mill. Minster Lovell. Oxford OX29 0TA. England.

Tel: +44 (0)1993 826050 / Fax: +44 (0)1993 824411 / Email: sales@jspsafety.com / Web: www.jspsafety.com

Do Not Publish without written permission from JSP Limited. Contact copyright@jspsafety.com. Information correct in the United Kingdom at date of issue and may be subject to change. Any third-party machine and automated translations processed by users may have inaccuracies and should not be relied upon.

