

2m Adjustable Work Positioning Lanyard with Rope Grab

2m Adjustable Work Positioning Lanyard with Rope Grab / FAR0420



DESCRIPTION

2m work positioning lanyard with non-openable aluminium rope grab with 2 screw gate connectors in alloy steel. Rope ends stitched and covered with polyethylene protective sleeve.

OPTIONS

2m Adjustable Work Positioning Lanyard with Rope Grab (FAR0420)

SAFETY STANDARDS

EN 358



SPECIFICATIONS

Length
2m Max.

Rope Ends
Stitched and Covered With Polyethylene Protective Sleeve. Abrasion Resistant Thimbles Provided Within Loops

Adjustment Device
Non Openable Rope Grab, Aluminium

Delivered With
2 Screwgate Connectors In Alloy Steel. Gate Opening 18mm. Conforms to EN362 Class B & M

Material
12mm High Quality Kernmantle Rope

Protective Rope Sleeve
60cm



Product Weight
1900g

DOWNLOADS

 [Image Pack \(ZIP\)](#)

 [doc-far0420-far0421.pdf \(PDF\)](#)



JSP Limited. Worsham Mill. Minster Lovell. Oxford OX29 0TA. England.

Tel: +44 (0)1993 826050 / Fax: +44 (0)1993 824411 / Email: sales@jspsafety.com / Web: www.jspsafety.com

Do Not Publish without written permission from JSP Limited. Contact copyright@jspsafety.com. Information correct in the United Kingdom at date of issue and may be subject to change. Any third-party machine and automated translations processed by users may have inaccuracies and should not be relied upon.

Page 2 of 2 / Issued 13 Dec 2025 / Copyright 2018 - 2025. JSP Limited. All Rights Reserved.

