# TECHNICAL SPECIFICATION



## 2m Adjustable Work Positioning Lanyard with Rope Grab

2m Adjustable Work Positioning Lanyard with Rope Grab / FAR0420



### DESCRIPTION

2m work positioning lanyard with non-openable aluminium rope grab with 2 screw gate connectors in alloy steel. Rope ends stitched and covered with polyethylene protective sleeve.

### OPTIONS

2m Adjustable Work Positioning Lanyard with Rope Grab (FAR0420)

#### SAFETY STANDARDS

EN 358















#### **SPECIFICATIONS**

Length

2m Max.

Rope Ends

Stitched and Covered With Polyethylene Protective Sleeve. Abrasion Resistant Thimbles Provided Within Loops

Adjustment Device

Non Openable Rope Grab, Aluminium

Delivered With

2 Screwgate Connectors In Alloy Steel. Gate Opening 18mm. Conforms to EN362 Class B & M

Material

12mm High Quality Kernmantle Rope

Protective Rope Sleeve

60cm



Product Weight

1900g

#### **APPLICATIONS**

General guidance only and should not be considered a substitute for a full risk assessment

Cranes Forms

Linesman

Steel Frame Telecomms

#### DOWNLOADS

Image Pack (ZIP)

doc-far0420-far0421.pdf (PDF)













