

2 m verstelbaar werkpositioneringskoord met touwgreep

2 m verstelbaar werkpositioneringskoord met touwgreep / FAR0420



BESCHRIJVING

Werkpositioneringslijn van 2 m met niet-openbare aluminium touwklem met 2 schroefkoppelingen in gelegeerd staal. Uiteinden van touw gestikt en bedekt met polyethyleen beschermhoes.

OPTIES

2 m verstelbaar werkpositioneringskoord met touwgreep (FAR0420)

VEILIGHEIDSNORMEN

EN 358



SPECIFICATIES

Lengte
2m Max.

Touwuiteinden
Gestikt en bedekt met polyethyleen beschermhoes.
Slijtvaste kousen voorzien in lussen

Afstelapparaat
Niet-openbare touwgreep, aluminium

Geleverd met
2 schroefgatverbindingen in gelegeerd staal.
Poortopening 18 mm. Voldoet aan EN362 Klasse B
& M

Materiaal
12mm Hoogwaardig Kernmanteltouw

Beschermende touwkoker
60cm



Gewicht product
1900g

DOWNLOADS

 [Pakket afbeeldingen \(ZIP\)](#)

 [doc-far0420-far0421.pdf \(PDF\)](#)



JSP Limited, Worsham Mill, Minster Lovell, Oxford OX29 0TA, England.

Tel: +44 (0)1993 826050 / Fax: +44 (0)1993 824411 / Email: sales@jspsafety.com / Web: www.jspsafety.com

Do Not Publish without written permission from JSP Limited. Contact copyright@jspsafety.com. Information correct in the United Kingdom at date of issue and may be subject to change. Any third-party machine and automated translations processed by users may have inaccuracies and should not be relied upon.

Page 2 of 2 / Issued 20 Apr 2026 / Copyright 2018 - 2026. JSP Limited. All Rights Reserved.

