

## 5m verstelbaar werkpositioneringskoord met touwgreep

5m verstelbaar werkpositioneringskoord met touwgreep / FAR0421



### BESCHRIJVING

5m werkpositioneringslijn met niet-openbare aluminium touwklem met 2 schroefkoppelingen in gelegeerd staal. Uiteinden van touw gestikt en bedekt met polyethyleen beschermhoes.

### OPTIES

**5m verstelbaar werkpositioneringskoord met touwgreep (FAR0421)**

### VEILIGHEIDSNORMEN

EN 358



## SPECIFICATIES

Lengte  
5m Max.

Touwuiteinden  
Gestikt en bedekt met polyethyleen beschermhoes.  
Slijtvaste kousen voorzien in lussen

Afstelapparaat  
Niet-openbare touwgreep Aluminium

Geleverd met  
2 schroefgatverbindingen in gelegeerd staal.  
Poortopening 18 mm. Voldoet aan EN 362 Klasse B  
& M

Materiaal  
12 mm hoge kwaliteit kermantouw

Beschermende touwkoker  
60cm



Gewicht product  
1170g

## DOWNLOADS

 [Pakket afbeeldingen \(ZIP\)](#)

 [doc-far0420-far0421.pdf \(PDF\)](#)



JSP Limited, Worsham Mill, Minster Lovell, Oxford OX29 0TA, England.

Tel: +44 (0)1993 826050 / Fax: +44 (0)1993 824411 / Email: sales@jspsafety.com / Web: www.jspsafety.com

Do Not Publish without written permission from JSP Limited. Contact copyright@jspsafety.com. Information correct in the United Kingdom at date of issue and may be subject to change. Any third-party machine and automated translations processed by users may have inaccuracies and should not be relied upon.

Page 2 of 2 / Issued 31 May 2026 / Copyright 2018 - 2026. JSP Limited. All Rights Reserved.

