

5m verstelbaar werkpositioneringskoord met touwgreep

5m verstelbaar werkpositioneringskoord met touwgreep / FAR0421



BESCHRIJVING

5m werkpositioneringslijn met niet-openbare aluminium touwklem met 2 schroefkoppelingen in gelegeerd staal. Uiteinden van touw gestikt en bedekt met polyethyleen beschermhoes.

OPTIES

5m verstelbaar werkpositioneringskoord met touwgreep (FAR0421)

VEILIGHEIDSNORMEN

EN 358



SPECIFICATIES

Lengte
5m Max.

Touwuiteinden
Gestikt en bedekt met polyethyleen beschermhoes.
Slijtvaste kousen voorzien in lussen

Afstelapparaat
Niet-openbare touwgreep Aluminium

Geleverd met
2 schroefgatverbindingen in gelegeerd staal.
Poortopening 18 mm. Voldoet aan EN 362 Klasse B
& M

Materiaal
12 mm hoge kwaliteit kernantouw

Beschermende touwkoker
60cm



Gewicht product
1170g

DOWNLOADS

 [Pakket afbeeldingen \(ZIP\)](#)

 [doc-far0420-far0421.pdf \(PDF\)](#)



JSP Limited, Worsham Mill, Minster Lovell, Oxford OX29 0TA, England.

Tel: +44 (0)1993 826050 / Fax: +44 (0)1993 824411 / Email: sales@jspsafety.com / Web: www.jspsafety.com

Do Not Publish without written permission from JSP Limited. Contact copyright@jspsafety.com. Information correct in the United Kingdom at date of issue and may be subject to change. Any third-party machine and automated translations processed by users may have inaccuracies and should not be relied upon.

Page 2 of 2 / Issued 15 Apr 2026 / Copyright 2018 - 2026. JSP Limited. All Rights Reserved.

