TECHNICAL SPECIFICATION



EVOGuard®C1 Industrial Visor

EVOGuard®C1 Industrial Visor / ADA240-060-000



DESCRIPTION

EVOGuard®C high performance industrial visors provide comprehensive facial coverage without limiting movement. The optical class 1 visor range offers UV protection and a panoramic view with minimal distortion.

Fully compatible with EVOGuard® browguard systems and *EVO® helmet models, the C1 visor offers up to AT rated impact protection and is also suitable for use with the Force®8 half mask and P3 filters.

*Excluding EVO®6100 and EVO® VISTA® ranges.

OPTIONS

EVOGuard®C1 Industrial Visor (ADA240-060-000)

SAFETY STANDARDS

EN 166 • EN 170





JSP Limited. Worsham Mill. Minster Lovell. Oxford OX29 0TA. England.

Tel: +44 (0)1993 826050 / Fax: +44 (0)1993 824411 / Email: sales@jspsafety.com / Web: www.jspsafety.com







SPECIFICATIONS



RADIATION PROTECTION BREAKDOWN filtering effect Scale Number

2C



Manufacturer's Trademark

JSP Dagger



High Energy Impact resists a 6 mm, 0.86g ball @ 190 m/s Maximum protection for face shields

A - When fitted to EVO® helmets



The letter T, immediately after the mechanical strength symbol, authorises use for high speed particles at extreme temperatures. (-5°C and +55°C) Optional

Resistance to Molten Metals and Hot Solids (optional)

Т



BSI Kitemark



Yes



Product Weight

185g

Kit



Supplied With: EVO® 2,3,5,DS,Lite,Skyworker™ Arms. EVO8/EVOLite Badgeholder Arms. **EVOGuard® Browguard Mounting System**

Lens Thickness - edge 1.70mm



LIGHT TRANSMISSION BREAKDOWN Lens Shade number



Optical Class (1 - Class 1 - High quality for regular use. 2 -Class 2 - Medium quality for occasional use. 3 - Class 3 -Low quality for exceptional use)



Medium Energy Impact resists a 6 mm, 0.86g ball @ 120 m/s Maximum protection for goggles.

B - When fitted to EVOGuard® browguard



Protection from Liquid Splash

3



Visor Length

18.5cm

Material

Polycarbonate Shield



Recyclable

Yes

Lens Thickness - centre

2.00mm

FEATURES



Compatibility

EVOGuard® visors maximise compatibility with JSP half masks, disposable respirators, prescription glasses and the Sonis® helmet mounted ear defender range.



Impact

Wide range of high performance visors offering up to A rated impact resistance when fitted to a safety helmet and medium energy impact protection with the EVOGuard® browquard.



UV Protection

Visor filters harmful UV radiation to protect the eyes whilst also offering high light transmission and enhanced colour recognition.



Vision

The optical class 1 visor offers a panoramic view with minimal distortion, ideal for comfortable all day wear.



Coverage

EVOGuard® visors provide comprehensive facial coverage without limiting movement. EVOGuard® MAX visors offer enhanced coverage with an integral chinquard.



Helmet & Browguard Integration

Compatible with EVO® helmet models and EVOGuard® browguard systems. Visor supplied with dual system clips for mounting to a helmet or browguard.

RANGE VIDEOS



www.youtube.com/watch?v=_VnTgBRRT9E





JSP Limited. Worsham Mill. Minster Lovell. Oxford OX29 0TA. England

Tel: +44 (0)1993 826050 / Fax: +44 (0)1993 824411 / Email: sales@jspsafety.com / Web: www.jspsafety.com

 $Do \ Not \ Publish \ without \ written \ permission \ from \ JSP \ Limited. \ Contact \ copyright@jspsafety.com. \ Information \ correct in the \ United \ Kingdom \ at \ Not \ Publish \ without \ written \ permission \ from \ JSP \ Limited.$ date of issue and may be subject to change. Any third-party machine and automated translations processed by users may have inaccuracies and should not be relied upon.







DOWNLOADS



Image Pack (ZIP)



doc-evoguard.pdf (PDF)





JSP Limited. Worsham Mill. Minster Lovell. Oxford OX29 0TA. England.

 $Tel: +44 \ (0) \\ 1993 \ 826050 \ / \ Fax: +44 \ (0) \\ 1993 \ 824411 \ / \ Email: \\ sales@jspsafety.com \ / \ Web: \\ www.jspsafety.com \ / \ Web: \\ www.js$





