

# EVO®2 Mid Peak OneTouch<sup>™</sup> Slip Ratchet Vented

White / AJF030-000-100



### DESCRIPTION

The EVO®2 Comfort Plus helmet combines a super strong shell for superior all day protection in the widest range of environments, with the comfort benefits of the new Evolution® 3D Adjustment<sup>™</sup> harness system. EVO®2 is a true evolution of the long-established MK®2 and MK®3 helmets. The EVO®2 retains the JSP signature styling while incorporating developments first seen in the EVO®8. Packed full of the latest protection technology and features.

## OPTIONS

Black (AJF030-001-100) Blue (AJF030-000-500) Green (AJF030-000-300) Grey - AJF030-000-400 - Made To Order Min 240 units (AJF030-000-400) Orange (AJF030-000-800) Pink (AJF030-000-800) Red (AJF030-000-800) White (AJF030-000-100) Yellow (AJF030-000-200)

#### SAFETY STANDARDS

EN 397



JSP Limited. Worsham Mill. Minster Lovell. Oxford OX29 0TA. England.

Tel: +44 (0)1993 826050 / Fax: +44 (0)1993 824411 / Email: sales@jspsafety.com / Web: www.jspsafety.com

Do Not Publish without written permission from JSP Limited. Contact copyright@jspsafety.com. Information correct in the United Kingdom at date of issue and may be subject to change. Any third-party machine and automated translations processed by users may have inaccuracies and should not be relied upon.

#### SPECIFICATIONS



Peak Mid Resistance to Molten Metals and Hot Solids (optional) Yes Minimum Temperature -30°C Recyclable Shell



Depth Adjustment **3D Harness** 



Universal Accessories Slot Yes



**BSI Kitemark** Yes

ID card holder

Optional



Product Weight 402g

## FEATURES



## **Firmest Fit Available**

The deep nape strap enables the firmest retention of any helmet, keeping it firmly rooted on the head. The OneTouch™ slip ratchet makes it simple to tighten to the perfect fit.



# **CR2 Reflective**

Using Class RA2, high intensity reflective. CR2 is the biggest step-up in night time visibility/reflectivity of head protection to date. Conforms to Class RA2, EN12899-1.



## Supreme Comfort

A traditional 6-point polyethylene harness making the EVO®2 the more economical choice, whilst still providing the same high performance as the EVO®3.



## **Ventilation Option**

Side and rear ventilation for optimum air movement inside the shell, reducing helmet temperatures by an average 2-3 degrees.

## LOGO

Front

Back



JSP Limited. Worsham Mill. Minster Lovell. Oxford OX29 0TA. England

Tel: +44 (0)1993 826050 / Fax: +44 (0)1993 824411 / Email: sales@jspsafety.com / Web: www.jspsafety.com

Do Not Publish without written permission from JSP Limited. Contact copyright@jspsafety.com. Information correct in the United Kingdom at date of issue and may be subject to change. Any third-party machine and automated translations processed by users may have inaccuracies and should not be relied upon.





50 Joules



Maximum Temperature +50°C

Impact Resistance



Yes



LDPE Harness Yes



Slip Ratchet Slip



Ventilation Yes

**Reflective Option** Optional



Size 53-64cm



## **3D Adjustment**

The polyethylene harness features unique 1-2-3 point depth settings. This offers the most precise fit attainable on an industrial safety helmet.

# Accessories

Universal attachment slot enables firm fitting of a range of safety visors and ear defenders.



## JSP Logo Express®

Strengthen your corporate identity by applying a company logo on a range of our safety helmets. Minimum order quantities and set-up charges apply.

RANGE



#### VIDEOS

www.youtube.com/watch?v=n9qrN2U0LFk

## DOWNLOADS

Image Pack (ZIP)

doc-invincible-evo2.pdf (PDF)



JSP Limited. Worsham Mill. Minster Lovell. Oxford OX29 0TA. England.

Tel: +44 (0)1993 826050 / Fax: +44 (0)1993 824411 / Email: sales@jspsafety.com / Web: www.jspsafety.com

Do Not Publish without written permission from JSP Limited. Contact copyright@jspsafety.com. Information correct in the United Kingdom at date of issue and may be subject to change. Any third-party machine and automated translations processed by users may have inaccuracies and should not be relied upon.