

# TECHNICAL SPECIFICATION



## Swiss One EIGER

1EIGLWB23CKN / 1EIGLWB23CKN



### DESCRIPTION

EIGER safety spectacles... Active style and sporty design! Unique Flexofit Technology engineered into temple cushioning padding to enhance wearer comfort, to provide a non-slip, low pressure fit. Excellence coating on this optimal curved lens, large field of vision, moulded browguard. Additional gasket & strap accessory pack available to deliver a perfect dust barrier.

Available in an amazing choice of colours to satisfy all wearers... classic, feminine, colourful... Sport or safety?... No need to choose you have all in one...! Try it... Enjoy it!

### OPTIONS

**1EIGLWB23CKN (1EIGLWB23CKN)**  
1EIGGREEN23CKN (1EIGGREEN23CKN)  
1EIGGREEN23SKN (1EIGGREEN23SKN)  
1EIGGREY23CKN (1EIGGREY23CKN)  
1EIGGREY23SKN (1EIGGREY23SKN)  
1EIGGY23CKN (1EIGGY23CKN)  
1EIGGY23SKN (1EIGGY23SKN)  
1EIGLWP23CKN (1EIGLWP23CKN)

### SAFETY STANDARDS

EN 170 • EN 166



JSP Limited. Worsham Mill. Minster Lovell. Oxford OX29 0TA. England.

Tel: +44 (0)1993 826050 / Fax: +44 (0)1993 824411 / Email: [sales@jspsafety.com](mailto:sales@jspsafety.com) / Web: [www.jspsafety.com](http://www.jspsafety.com)

Do Not Publish without written permission from JSP Limited. Contact [copyright@jspsafety.com](mailto:copyright@jspsafety.com). Information correct in the United Kingdom at date of issue and may be subject to change. Any third-party machine and automated translations processed by users may have inaccuracies and should not be relied upon.

Page 1 of 2 / Issued 16 Jul 2025 / Copyright 2018 - 2025. JSP Limited. All Rights Reserved.



## SPECIFICATIONS



**RADIATION PROTECTION BREAKDOWN** filtering effect  
Scale Number  
2C



**LIGHT TRANSMISSION BREAKDOWN** Lens Shade number  
1.2



Manufacturer's Trademark  
**Swiss One**



Low Energy Impact resists a 6 mm, 0.86g ball @ 45 m/s °  
Maximum protection for glasses  
F



Optical Class (1 – Class 1 – High quality for regular use. 2 – Class 2 – Medium quality for occasional use. 3 – Class 3 – Low quality for exceptional use)  
1



Resistance to Surface Damage by Fine Particles (optional)  
K



The letter T, immediately after the mechanical strength symbol, authorises use for high speed particles at extreme temperatures. (-5°C and +55°C) Optional  
T



Resistance to fogging (optional)  
N

Excellence Coating (KN Anti-Scratch/Anti-Mist)  
Yes

Flex Nose Bridge  
Yes

Lens Base Curve  
9

Metal Free (Di Electric)  
Yes

Soft End Tips - Flex Flat Temple Pressure Free  
Yes



Product Weight  
31g

FLEXoFIT Technology  
Yes

## FEATURES



### Flex Nose Bridge

Flex nose bridge



### Soft Nose Pad

Soft nose pad



### Soft End Tips

Soft end tips



### Lens Curve

Lens curve



### Metal free

Metal free



### High Performance Coating

Anti-scratch / anti-fog high performance coating



### Flexofit Technology

Flexofit technology

## RANGE



## DOWNLOADS



[Image Pack \(ZIP\)](#)



[doc-eiger.pdf \(PDF\)](#)



JSP Limited. Worsham Mill. Minster Lovell. Oxford OX29 0TA. England.

Tel: +44 (0)1993 826050 / Fax: +44 (0)1993 824411 / Email: [sales@jsp-safety.com](mailto:sales@jsp-safety.com) / Web: [www.jsp-safety.com](http://www.jsp-safety.com)

Do Not Publish without written permission from JSP Limited. Contact [copyright@jsp-safety.com](mailto:copyright@jsp-safety.com). Information correct in the United Kingdom at date of issue and may be subject to change. Any third-party machine and automated translations processed by users may have inaccuracies and should not be relied upon.

Page 2 of 2 / Issued 16 Jul 2025 / Copyright 2018 - 2025. JSP Limited. All Rights Reserved.

