

# TECHNICAL SPECIFICATION



## Stealth™ Hybrid

Stealth™Hybrid replacement clear lens (KN) / ASB450-051-300



### DESCRIPTION

Functions as either a safety spectacle or a safety goggle once the arms have been disconnected and the strap has been attached. Supplied with goggle strap and a set of spectacle arms.

### OPTIONS

Stealth™ Hybrid (ASA450-151-102)

**Stealth™Hybrid replacement clear lens (KN)  
(ASB450-051-300)**

Stealth™Hybrid replacement smoke lens (KN)  
(ASB450-0A3-000)

### SAFETY STANDARDS

EN 166 • EN 170



JSP Limited. Worsham Mill. Minster Lovell. Oxford OX29 0TA. England.

Tel: +44 (0)1993 826050 / Fax: +44 (0)1993 824411 / Email: sales@jspsafety.com / Web: www.jspsafety.com

Do Not Publish without written permission from JSP Limited. Contact copyright@jspsafety.com. Information correct in the United Kingdom at date of issue and may be subject to change. Any third-party machine and automated translations processed by users may have inaccuracies and should not be relied upon.

Page 1 of 2 / Issued 11 May 2025 / Copyright 2018 - 2025. JSP Limited. All Rights Reserved.



## SPECIFICATIONS



**RADIATION PROTECTION BREAKDOWN** filtering effect  
Scale Number  
2C - Clear lens 5 - Smoke lens



**LIGHT TRANSMISSION BREAKDOWN** Lens Shade number  
1.2- Clear lens 2.5 - Smoke lens



Optical Class (1 – Class 1 – High quality for regular use. 2 – Class 2 – Medium quality for occasional use. 3 – Class 3 – Low quality for exceptional use)  
1



Medium Energy Impact resists a 6 mm, 0.86g ball @ 120 m/s Maximum protection for goggles.  
B - When Fitted With Goggle Strap



Low Energy Impact resists a 6 mm, 0.86g ball @ 45 m/s °  
Maximum protection for glasses  
F - When Fitted With Side Arms



Resistance to Surface Damage by Fine Particles (optional)  
K



Resistance to fogging (optional)  
N



The letter T, immediately after the mechanical strength symbol, authorises use for high speed particles at extreme temperatures. (-5°C and +55°C) Optional  
T- When fitted with side arms

## FEATURES



### Adjustable Arms

Spectacle arms can be clipped into the frame to create the safety spectacle. Pantoscopic angle adjustment allows the frame to be angled to offer a customised fit.



### EVA Foam Seal

EVA foam provides comfort on the bridge of the nose and around the eyes whilst providing ventilation.



### Changeable Lens

The changeable lens allows users to replace the lens according to different applications.

## RANGE

**STEALTH  
HYBRID**

## DOWNLOADS



[Image Pack \(ZIP\)](#)



[doc-stealth-hybrid.pdf \(PDF\)](#)



JSP Limited. Worsham Mill. Minster Lovell. Oxford OX29 0TA. England.

Tel: +44 (0)1993 826050 / Fax: +44 (0)1993 824411 / Email: [sales@jsp-safety.com](mailto:sales@jsp-safety.com) / Web: [www.jsp-safety.com](http://www.jsp-safety.com)

Do Not Publish without written permission from JSP Limited. Contact [copyright@jsp-safety.com](mailto:copyright@jsp-safety.com). Information correct in the United Kingdom at date of issue and may be subject to change. Any third-party machine and automated translations processed by users may have inaccuracies and should not be relied upon.

Page 2 of 2 / Issued 11 May 2025 / Copyright 2018 - 2025. JSP Limited. All Rights Reserved.

