

SPECYFIKACJA TECHNICZNA



Wyciągarka

Wyciągarka / FAR1004



OPIS

Wyciągarka do miejsc zamkniętych z integralnym systemem hamowania, wyposażona w mechanizm: obrotowy uchwyt do podnoszenia lub opuszczania, stalowe złącze śrubowe oraz płytę montażową do zamocowania na trójnogu lub innym wsporniku. Max. długość 20m. Ładowność znamionowa 135kg.

OPCJE

Wyciągarka (FAR1004)

NORMY BEZPIECZEŃSTWA

EN 1496



JSP Limited, Worsham Mill, Minster Lovell, Oxford OX29 0TA, England.

Tel: +44 (0)1993 826050 / Fax: +44 (0)1993 824411 / Email: sales@jspsafety.com / Web: www.jspsafety.com

Do Not Publish without written permission from JSP Limited. Contact copyright@jspsafety.com. Information correct in the United Kingdom at date of issue and may be subject to change. Any third-party machine and automated translations processed by users may have inaccuracies and should not be relied upon.

Page 1 of 2 / Issued 16 May 2026 / Copyright 2018 - 2026. JSP Limited. All Rights Reserved.



SPECYFIKACJE



Waga Produktu
7500g

PLIKI DO POBRANIA



[Zbiór zdjęć \(ZIP\)](#)



[doc-far1004.pdf \(PDF\)](#)



JSP Limited. Worsham Mill. Minster Lovell. Oxford OX29 0TA. England.

Tel: +44 (0)1993 826050 / Fax: +44 (0)1993 824411 / Email: sales@jspsafety.com / Web: www.jspsafety.com

Do Not Publish without written permission from JSP Limited. Contact copyright@jspsafety.com. Information correct in the United Kingdom at date of issue and may be subject to change. Any third-party machine and automated translations processed by users may have inaccuracies and should not be relied upon.

Page 2 of 2 / Issued 16 May 2026 / Copyright 2018 - 2026. JSP Limited. All Rights Reserved.

