TECHNISCHE SPEZIFIKATION

EVOGuard®C Industrielles Kopfteil (nur)

EVOGuard®C Industrielles Kopfteil (nur) / ADB280-000-400



BESCHREIBUNG

EVOGuard®C Industrial Browguard for use with *EVOGuard® visors, providing innovative solutions to protect the wearer in a multitude of high-risk working environments.

The EVOGuard®C Industrial Browguard meets the requirements of EN 166 and EN 1731 when fitted with the appropriate EVOGuard® visor.

*EVOGuard® C5 Max visor for use with EVO® helmets only.

OPTIONEN

EVOGuard®C Industrielles Kopfteil (nur) (ADB280-000-400)

SICHERHEITSSTANDARDS

EN 166 • EN 1731

JSP Limited. Worsham Mill. Minster Lovell. Oxford OX29 0TA. England.

Tel: +44 (0)1993 826050 / Fax: +44 (0)1993 824411 / Email: sales@jspsafety.com / Web: www.jspsafety.com

Do Not Publish without written permission from JSP Limited. Contact copyright@jspsafety.com. Information correct in the United Kingdom at date of issue and may be subject to change. Any third-party machine and automated translations processed by users may have inaccuracies and should not be relied upon.

SPEZIFIKATIONEN

Innenausstattung
NEUE Scharniere. Auf 6 Positionen einstellbares Kopfband Extra langes Schweißband.

Drehradverschluss
Ja NEUES dämpfendes Komfortpolster

Wiederverwendbar
Ja

Material
30% Glasfaser-Nylon

Stoßfestigkeit
BT

Universeller Zubehör-Steckplatz
Ja

Integrierter Augenschutz
Optional EvoSpec

BSI Kitemark
Ja

Produktgewicht
210g

EIGENSCHAFTEN



Kompatibilität

EVOGuard® Visiere maximieren die Kompatibilität mit JSP-Halbmasken, Einweg-Atemschutzmasken, Korrekturgläsern und der Sonis®-Gehörschützerserie.




Aufprall

Wide range of high performance visors offering up to A rated impact resistance when fitted to a safety helmet and medium energy impact protection with the EVOGuard® browguard.



Höchste(r) Komfort & Passform

Ausgestattet mit dem neuen JSP Revolution® Drehrad, der die Einheit sicher festzieht und in Position hält, unabhängig von der Aufgabe oder dem Ausmaß der Benutzerbewegung. Das System wird komplett mit einem umlaufenden, weichen, mit Schaumstoff hinterlegten, austauschbaren Chamlon™ Schweißband geliefert, das höchsten Komfort bietet.



Sicht

Das optische Visier der Klasse 1 bietet einen Panoramablick mit minimaler Verzerrung, ideal für komfortables ganztägiges Tragen.



Abdeckung

Die Visiere von EVOGuard® bieten eine umfassende Gesichtsabdeckung ohne Bewegungseinschränkung. EVOGuard® MAX-Visiere bieten eine verbesserte Abdeckung mit einem integrierten Kinnschutz.



Maximale Justierbarkeit

Der Träger kann den Gesichtsschutz mit Hilfe der speziellen Höhenverstellung einfach auf drei Arten einstellen. Ein großes hinteres Komfortpolster passt sich der Kopfform des Trägers an, verteilt die Last und sitzt unter dem Hinterhauptbein für einen besonders sicheren Sitz.

SERIE

EVOGUARD C
INDUSTRIAL RANGE

DOWNLOADS

Bilderordner (ZIP)
doc-evoguard.pdf (PDF)

JSP Limited. Worsham Mill. Minster Lovell. Oxford OX29 0TA. England.

Tel: +44 (0)1993 826050 / Fax: +44 (0)1993 824411 / Email: sales@jspsafety.com / Web: www.jspsafety.com

Do Not Publish without written permission from JSP Limited. Contact copyright@jspsafety.com. Information correct in the United Kingdom at date of issue and may be subject to change. Any third-party machine and automated translations processed by users may have inaccuracies and should not be relied upon.