

TECHNICAL SPECIFICATION



EVOGuard®C Industrial Browguard Only

EVOGuard®C Industrial Browguard Only / ADB280-000-400



DESCRIPTION

EVOGuard®C Industrial Browguard for use with *EVOGuard® visors, providing innovative solutions to protect the wearer in a multitude of high-risk working environments.

The EVOGuard®C Industrial Browguard meets the requirements of EN 166 and EN 1731 when fitted with the appropriate EVOGuard® visor.

*EVOGuard® C5 Max visor for use with EVO® helmets only.

OPTIONS

**EVOGuard®C Industrial Browguard Only
(ADB280-000-400)**

SAFETY STANDARDS

EN 166 • EN 1731



JSP Limited, Worsham Mill, Minster Lovell, Oxford OX29 0TA, England.

Tel: +44 (0)1993 826050 / Fax: +44 (0)1993 824411 / Email: sales@jspsafety.com / Web: www.jspsafety.com

Do Not Publish without written permission from JSP Limited. Contact copyright@jspsafety.com. Information correct in the United Kingdom at date of issue and may be subject to change. Any third-party machine and automated translations processed by users may have inaccuracies and should not be relied upon.

Page 1 of 2 / Issued 2 Aug 2025 / Copyright 2018 - 2025. JSP Limited. All Rights Reserved.



SPECIFICATIONS

Harness
NEW Rake. 6 positions. sizing strap over head.
Extra long sweat band.



Universal Accessories Slot
Yes



Wheel Ratchet
Yes NEW Sprung comfort pad



Integrated Eyewear
Optional EvoSpec



Recyclable
Yes



BSI Kitemark
Yes

Material
30% Glass Filled Nylon



Product Weight
210g



Impact Resistance
BT

FEATURES



Compatibility

EVOGuard® visors maximise compatibility with JSP half masks, disposable respirators, prescription glasses and the Sonis® helmet mounted ear defender range.



Vision

The optical class 1 visor offers a panoramic view with minimal distortion, ideal for comfortable all day wear.



Impact

Wide range of high performance visors offering up to A rated impact resistance when fitted to a safety helmet and medium energy impact protection with the EVOGuard® browguard.



Coverage

EVOGuard® visors provide comprehensive facial coverage without limiting movement. EVOGuard® MAX visors offer enhanced coverage with an integral chinguard.



Supreme Comfort & Fit

Features the new JSP Revolution® wheel ratchet, securely tightening and holding the unit firmly in position, no matter the task or amount of user movement involved. System comes complete with a wraparound, soft foam backed, replaceable, Chamlon™ sweatband offers superior comfort.



Maximum Adjustability

Multiple fitting positions allow the wearer to adjust the browguard in three ways. An over the crown slide fitting combined with a forward and back adjustment, maximises compatibility with different head shapes.

RANGE



DOWNLOADS



[Image Pack \(ZIP\)](#)



[doc-evoguard.pdf \(PDF\)](#)



JSP Limited. Worsham Mill. Minster Lovell. Oxford OX29 0TA. England.

Tel: +44 (0)1993 826050 / Fax: +44 (0)1993 824411 / Email: sales@jsp-safety.com / Web: www.jsp-safety.com

Do Not Publish without written permission from JSP Limited. Contact copyright@jsp-safety.com. Information correct in the United Kingdom at date of issue and may be subject to change. Any third-party machine and automated translations processed by users may have inaccuracies and should not be relied upon.

Page 2 of 2 / Issued 2 Aug 2025 / Copyright 2018 - 2025. JSP Limited. All Rights Reserved.

