

ESPECIFICACIONES TÉCNICAS



EVOGuard®C Arnés (solo)

EVOGuard®C Arnés (solo) / ADB280-000-400



DESCRIPCIÓN

EVOGuard®C Industrial Browguard for use with *EVOGuard® visors, providing innovative solutions to protect the wearer in a multitude of high-risk working environments.

The EVOGuard®C Industrial Browguard meets the requirements of EN 166 and EN 1731 when fitted with the appropriate EVOGuard® visor.

*EVOGuard® C5 Max visor for use with EVO® helmets only.

OPCIONES

EVOGuard®C Arnés (solo) (ADB280-000-400)

NORMAS DE SEGURIDAD

EN 166 • EN 1731



JSP Limited, Worsham Mill, Minster Lovell, Oxford OX29 0TA, England.

Tel: +44 (0)1993 826050 / Fax: +44 (0)1993 824411 / Email: sales@jgpsafety.com / Web: www.jgpsafety.com

Do Not Publish without written permission from JSP Limited. Contact copyright@jgpsafety.com. Information correct in the United Kingdom at date of issue and may be subject to change. Any third-party machine and automated translations processed by users may have inaccuracies and should not be relied upon.

Page 1 of 2 / Issued 18 Jun 2026 / Copyright 2018 - 2026. JSP Limited. All Rights Reserved.



ESPECIFICACIONES

Arnés
NUEVO rastrillo. 6 posiciones. Cinta de tallaje sobre la cabeza. Banda de sudor extra larga.



Ranura para accesorios universales
Sí



Ajuste con rueda
Sí NUEVA almohadilla de confort



Gafas Integradas
EvoSpec opcional



Reciclable
Sí



Certificado BSI Kitemark
Sí

Material
30% de nylon cargado con vidrio



Peso del producto
210g

CARACTERÍSTICAS



Compatibilidad

Las pantallas EVOGuard® maximizan la compatibilidad con las semi-máscaras JSP, respiradores desechables, gafas graduadas y la gama de protectores auditivos montados en casco Sonis®.



Visión

El visor de clase óptica 1 ofrece una vista panorámica con una distorsión mínima, ideal para el uso cómodo durante todo el día.



Impacto

Wide range of high performance visors offering up to A rated impact resistance when fitted to a safety helmet and medium energy impact protection with the EVOGuard® browguard.



Cobertura

Las pantallas EVOGuard® proporcionan una cobertura facial completa sin limitar el movimiento. Las pantallas EVOGuard® MAX ofrecen una cobertura mejorada con un barbuquejo integral.



Comodidad suprema

Cuenta con el nuevo ajuste de rueda JSP Revolution®, que mantiene la unidad firmemente en su posición, sin importar la tarea o la intensidad de movimiento del usuario. El sistema viene completo con un acolchado envolvente de espuma suave y extraíble, la banda antisudor Chamlon™ ofrece mayor comodidad.



Máxima capacidad de ajuste

Múltiples posiciones de ajuste permiten al usuario regular el arnés de tres maneras. El ajuste deslizante sobre la corona combinado con un ajuste hacia adelante y hacia atrás optimizan la compatibilidad con diferentes formas de cabeza.

GAMA



DESCARGAR



[Colección de imágenes \(ZIP\)](#)



[doc-evoguard.pdf \(PDF\)](#)



JSP Limited, Worsham Mill, Minster Lovell, Oxford OX29 0TA, England.

Tel: +44 (0)1993 826050 / Fax: +44 (0)1993 824411 / Email: sales@jsspsafety.com / Web: www.jsspsafety.com

Do Not Publish without written permission from JSP Limited. Contact copyright@jsspsafety.com. Information correct in the United Kingdom at date of issue and may be subject to change. Any third-party machine and automated translations processed by users may have inaccuracies and should not be relied upon.

Page 2 of 2 / Issued 18 Jun 2026 / Copyright 2018 - 2026. JSP Limited. All Rights Reserved.

