

# TECHNICAL SPECIFICATION



## Swiss One MAXVIEW

3MAX23CREP / 1MAX23CREP



### DESCRIPTION

Lens options to meet your requirements. Thanks to its easy swap lens system, the model MAXVIEW adapts itself to your needs. Available complete in a clear lens version, you then have the option of ordering replacement lenses in clear, yellow, smoke or polarized. RX insert available for prescription lenses.

### OPTIONS

**3MAX23CREP (1MAX23CREP)**  
3MAX21POL3.1 (3MAX21POL3.1)  
3MAX23Y (3MAX23Y)

### SAFETY STANDARDS

EN 170 • EN 166



JSP Limited, Worsham Mill, Minster Lovell, Oxford OX29 0TA, England.

Tel: +44 (0)1993 826050 / Fax: +44 (0)1993 824411 / Email: [sales@jsp-safety.com](mailto:sales@jsp-safety.com) / Web: [www.jsp-safety.com](http://www.jsp-safety.com)

Do Not Publish without written permission from JSP Limited. Contact [copyright@jsp-safety.com](mailto:copyright@jsp-safety.com). Information correct in the United Kingdom at date of issue and may be subject to change. Any third-party machine and automated translations processed by users may have inaccuracies and should not be relied upon.

Page 1 of 2 / Issued 20 Feb 2025 / Copyright 2018 - 2025. JSP Limited. All Rights Reserved.



## SPECIFICATIONS



**RADIATION PROTECTION BREAKDOWN** filtering effect  
Scale Number  
2C



**LIGHT TRANSMISSION BREAKDOWN** Lens Shade number  
1.2



Manufacture's Trademark Swiss One  
**Swiss One**



Optical Class (1 – Class 1 – High quality for regular use. 2 – Class 2 – Medium quality for occasional use. 3 – Class 3 – Low quality for exceptional use)  
1



Low Energy Impact resists a 6 mm, 0.86g ball @ 45 m/s °  
Maximum protection for glasses  
F



The letter T, immediately after the mechanical strength symbol, authorises use for high speed particles at extreme temperatures. (-5°C and +55°C) Optional  
T

Anti-Scratch/Anti-Fog Coating (23)  
Yes

Soft Nose Pad  
Yes

Soft End Tips - Flex Flat Temple Pressure Free  
Yes



Product Weight  
24g

RX Insert  
Maxviewinsert Compatible

## FEATURES



### Anti-mist

Anti-mist



### Anti-scratch

Anti-scratch



### Soft Nose Pad

Soft nose pad



### Soft End Tips

Soft end tips



### UV 400 Absorption

UV 400 absorption



### RX Insert Compatible

RX Insert compatible

## RANGE



## DOWNLOADS

[Image Pack \(ZIP\)](#)

[doc-maxview.pdf \(PDF\)](#)



JSP Limited, Worsham Mill, Minster Lovell, Oxford OX29 0TA, England.

Tel: +44 (0)1993 826050 / Fax: +44 (0)1993 824411 / Email: sales@jsp-safety.com / Web: www.jsp-safety.com

Do Not Publish without written permission from JSP Limited. Contact copyright@jsp-safety.com. Information correct in the United Kingdom at date of issue and may be subject to change. Any third-party machine and automated translations processed by users may have inaccuracies and should not be relied upon.

Page 2 of 2 / Issued 20 Feb 2025 / Copyright 2018 - 2025. JSP Limited. All Rights Reserved.

