# ESPECIFICACIONES TÉCNICAS



# Swiss One MAXVIEW

3MAX23CREP / 1MAX23CREP



## DESCRIPCIÓN

Lens options to meet your requirements. Thanks to it's easy swap lens system, the model MAXVIEW adapts itself to your needs. Available complete in a clear lens version, you then have the option of ordering replacement lenses in clear, yellow, smoke or polarized. RX insert available for prescription lenses.

#### **OPCIONES**

## 3MAX23CREP (1MAX23CREP)

3MAX21POL3.1 (3MAX21POL3.1) 3MAX23Y (3MAX23Y)

# NORMAS DE SEGURIDAD

EN 170 • EN 166















#### **ESPECIFICACIONES**



RADIATION PROTECTION BREAKDOWN filtering effect Scale Number

2C



Manufacture's Trademark Swiss One

Swiss One



Low Energy Impact resists a 6 mm, 0.86g ball @ 45 m/s ° Maximum protection for glasses

Anti-Scratch/Anti-Fog Coating (23)

Soft End Tips - Flex Flat Temple Pressure Free



**Product Weight** 

24g



LIGHT TRANSMISSION BREAKDOWN Lens Shade number 1,2



Optical Class (1 - Class 1 - High quality for regular use. 2 -Class 2 - Medium quality for occasional use. 3 - Class 3 -Low quality for exceptional use)



The letter T, immediately after the mechanical strength symbol, authorises use for high speed particles at extreme temperatures. (-5°C and +55°C) Optional

Т

Soft Nose Pad

Sí

**RX** Insert

Maxview insert Compatible

#### CARACTERÍSTICAS









Anti-mist









Soft nose pad





**UV 400 Absorption** 

UV 400 absorption





#### Anti-scratch

Anti-scratch





**Soft End Tips** 

Soft end tips





#### **RX Insert Compatible**

RX Insert compatible

# GAMA



# DESCARGAR

Colección de imágenes (ZIP)

doc-maxview.pdf (PDF)







Tel: +44 (0)1993 826050 / Fax: +44 (0)1993 824411 / Email: sales@jspsafety.com / Web: www.jspsafety.com





