

# SPECYFIKACJA TECHNICZNA



## Swiss One MAXVIEW

3MAX23CREP / 1MAX23CREP



### OPIS

Różne opcje soczewek, aby spełnić Twoje wymagania. Dzięki łatwemu systemowi wymiany soczewek model MAXVIEW dostosowuje się do Twoich potrzeb. Dostępne w wersji z przezroczystymi soczewkami, można zamówić soczewki zamienne w wersji przezroczystej, żółtej, przyciemnionej lub polaryzacyjnej. Dostępna wkładka RX.

### OPCJE

**3MAX23CREP (1MAX23CREP)**  
3MAX21POL3.1 (3MAX21POL3.1)  
3MAX23Y (3MAX23Y)

### NORMY BEZPIECZEŃSTWA

EN 170 • EN 166



JSP Limited, Worsham Mill, Minster Lovell, Oxford OX29 0TA, England.

Tel: +44 (0)1993 826050 / Fax: +44 (0)1993 824411 / Email: sales@jspsafety.com / Web: www.jspsafety.com

Do Not Publish without written permission from JSP Limited. Contact copyright@jspsafety.com. Information correct in the United Kingdom at date of issue and may be subject to change. Any third-party machine and automated translations processed by users may have inaccuracies and should not be relied upon.

Page 1 of 2 / Issued 20 Feb 2025 / Copyright 2018 - 2025. JSP Limited. All Rights Reserved.



## SPECYFIKACJE



RADIATION PROTECTION BREAKDOWN filtering effect  
Scale Number  
2C



Manufacture's Trademark Swiss One  
**Swiss One**



Low Energy Impact resists a 6 mm, 0.86g ball @ 45 m/s °  
Maximum protection for glasses  
**F**

Anti-Scratch/Anti-Fog Coating (23)  
**Tak**

Soft End Tips - Flex Flat Temple Pressure Free  
**Tak**



Product Weight  
24g



LIGHT TRANSMISSION BREAKDOWN Lens Shade number  
1,2



Optical Class (1 – Class 1 – High quality for regular use. 2 – Class 2 – Medium quality for occasional use. 3 – Class 3 – Low quality for exceptional use)  
**1**



The letter T, immediately after the mechanical strength symbol, authorises use for high speed particles at extreme temperatures. (-5°C and +55°C) Optional  
**T**

Soft Nose Pad  
**Tak**

RX Insert  
Kompatybilne z wkładkami Maxview

## CECHY



### Nieparujące

Nieparujące



### Miękki mostek nosowy

Miękki mostek nosowy



### Absorpcja promieni UV 400

Absorpcja promieni UV 400



### Nierysujące

Nierysujące



### Miękkie końcówki

Miękkie końcówki



### Kompatybilne z wkładkami RX

Kompatybilne z wkładkami RX

## GAMA



## PLIKI DO POBRANIA

[Zbiór zdjęć \(ZIP\)](#)

[doc-maxview.pdf \(PDF\)](#)



JSP Limited, Worsham Mill, Minster Lovell, Oxford OX29 0TA, England.

Tel: +44 (0)1993 826050 / Fax: +44 (0)1993 824411 / Email: sales@jsp-safety.com / Web: www.jsp-safety.com

Do Not Publish without written permission from JSP Limited. Contact copyright@jsp-safety.com. Information correct in the United Kingdom at date of issue and may be subject to change. Any third-party machine and automated translations processed by users may have inaccuracies and should not be relied upon.

Page 2 of 2 / Issued 20 Feb 2025 / Copyright 2018 - 2025. JSP Limited. All Rights Reserved.

