

ESPECIFICACIONES TÉCNICAS



Swiss One Onex

1ONEBO23CKN / 1ONEBO23CKN



DESCRIPCIÓN

This exciting eyewear combines innovative technology and unique fit concepts. Adjustable Flexofit nosebridge with 3 click adjustment positions to fit all nose widths. One of the lightest eyewear products at 23g. Integrated browguard for comfort and protection as well as pantoscopic temples with soft non-slip temple tips for extra grip. All in one for your best choice!

OPCIONES

1ONEBFG23CKN (1ONEBFG23CKN)
1ONEBLG23CKN (1ONEBLG23CKN)
1ONEBO23CKN (1ONEBO23CKN)
Onex 10NEBO23SKN (10NEBO23SKN)

NORMAS DE SEGURIDAD

EN 170 • EN 166



JSP Limited. Worsham Mill. Minster Lovell. Oxford OX29 0TA. England.

Tel: +44 (0)1993 826050 / Fax: +44 (0)1993 824411 / Email: sales@jspsafety.com / Web: www.jspsafety.com

Do Not Publish without written permission from JSP Limited. Contact copyright@jspsafety.com. Information correct in the United Kingdom at date of issue and may be subject to change. Any third-party machine and automated translations processed by users may have inaccuracies and should not be relied upon.

Page 1 of 2 / Issued 29 May 2025 / Copyright 2018 - 2025. JSP Limited. All Rights Reserved.



ESPECIFICACIONES



PROTECCIÓN RADIOLÓGICA Valor de escala de efecto de filtrado
2C



Marca del fabricante Swiss One
Swiss One



El impacto de baja energía resiste una bola de 6 mm, 0,86 g a 45 m/s de Máxima protección para gafas
F



Resistencia al daño superficial por partículas finas (opcional)
K

Revestimiento Excellence (KN Anti-Rayado/Anti-Niebla)
Sí

Ligero
Sí

Brazos laterales giratorios
Sí

Tecnología Flexofit
Sí



TRANSMISIÓN DE LA LUZ Valor de oscurecimiento de lente
1,2



Clase óptica (1- Clase 1- alta calidad para uso regular. 2 - Clase 2 - calidad media para uso ocasional. 3 - Clase 3- calidad baja para un uso excepcional).
1



La letra T, inmediatamente después del símbolo de resistencia mecánica, autoriza el uso de partículas de alta velocidad a temperaturas extremas. (-5° y +55°c) opcional
T



Resistencia al empañamiento (opcional)

Curva de la base de la lente
9

Puente nasal flexible
Sí

Puntas blandas - Templo plano flexible sin presión
Sí



Peso del producto
23g

CARACTERÍSTICAS



Anti-mist

Anti-mist



Lens Curve

Lens curve



Lightweight

Lightweight



Rotating Arms

Rotating arms



Flexofit Technology

Flexofit technology



Anti-scratch

Anti-scratch



High Performance Coating

Anti-scratch / anti-fog high performance coating



Nose Bridge Adjustment

Nose bridge adjustment



Soft End Tips

Soft end tips

GAMA



DESCARGAR



[Colección de imágenes \(ZIP\)](#)



[doc-onex.pdf \(PDF\)](#)



JSP Limited. Worsham Mill. Minster Lovell. Oxford OX29 0TA. England.

Tel: +44 (0)1993 826050 / Fax: +44 (0)1993 824411 / Email: sales@jspsafety.com / Web: www.jspsafety.com

Do Not Publish without written permission from JSP Limited. Contact copyright@jspsafety.com. Information correct in the United Kingdom at date of issue and may be subject to change. Any third-party machine and automated translations processed by users may have inaccuracies and should not be relied upon.

Page 2 of 2 / Issued 29 May 2025 / Copyright 2018 - 2025. JSP Limited. All Rights Reserved.

