

Swiss One RIGI LADY

1RIGLABB21AR / 1RIGLABB21AR



DESCRIPTION

Whatever is your workplace environment, RIGI delivers the perfect association of performance, safety and active style. The unique close fitting design, ultra light weight... 19gr of comfort and fit, wide field of vision and a design fitting women's faces

OPTIONS

1RIGLABB21AR (1RIGLABB21AR)

SAFETY STANDARDS

EN 170 • EN 166



JSP Limited. Worsham Mill. Minster Lovell. Oxford OX29 0TA. England.

Tel: +44 (0)1993 826050 / Fax: +44 (0)1993 824411 / Email: sales@jspsafety.com / Web: www.jspsafety.com

Do Not Publish without written permission from JSP Limited. Contact copyright@jspsafety.com. Information correct in the United Kingdom at date of issue and may be subject to change. Any third-party machine and automated translations processed by users may have inaccuracies and should not be relied upon.

SPECIFICATIONS



RADIATION PROTECTION BREAKDOWN filtering effect Scale Number 2C



Manufacture's Trademark Swiss One Swiss One



Low Energy Impact resists a 6 mm, 0.86g ball @ 45 m/s ° Maximum protection for glasses F

Blue Blocker Anti- Reflective Lens Yes

Flex Nose Bridge

Flex Nose Bridge

Vision+ Lens 66% Visual Clarity

Lightweight Yes

FLEXoFIT Technology Yes



FEATURES			
	Anti-scratch Anti-scratch	(9.5)	Lens Curve
\otimes	High Performance Coating Anti-scratch / anti-fog high performance coating	0	Soft End Tips
	Flexofit Technology		Soft Nose Pad





DOWNLOADS

<u>)</u>

1.2

1

Т

9.5

Yes

Yes

19g

Lens Base Curve

Product Weight

Image Pack (ZIP)

LIGHT TRANSMISSION BREAKDOWN Lens Shade number

Optical Class (1 - Class 1 - High quality for regular use. 2 -Class 2 - Medium quality for occasional use. 3 - Class 3 -

The letter T, immediately after the mechanical strength

symbol, authorises use for high speed particles at extreme

Low quality for exceptional use)

Anti-Scratch Coating (21 Code)

temperatures. (-5°C and +55°C) Optional

Soft End Tips - Flex Flat Temple Pressure Free

doc-rigi.pdf (PDF)



JSP Limited. Worsham Mill. Minster Lovell. Oxford OX29 0TA. England.

Tel: +44 (0)1993 826050 / Fax: +44 (0)1993 824411 / Email: sales@jspsafety.com / Web: www.jspsafety.com

Do Not Publish without written permission from JSP Limited. Contact copyright@jspsafety.com. Information correct in the United Kingdom at date of issue and may be subject to change. Any third-party machine and automated translations processed by users may have inaccuracies and should not be relied upon.

