

# TECHNICAL SPECIFICATION



## Aluminium Tower Hook

Aluminium Tower Hook / FAR0908



### DESCRIPTION

Auto closing and auto locking type tower / rebar hook in aluminium alloy silver. Breaking load 20kN.

### OPTIONS

**Aluminium Tower Hook (FAR0908)**

### SAFETY STANDARDS

EN 362



JSP Limited, Worsham Mill, Minster Lovell, Oxford OX29 0TA, England.

Tel: +44 (0)1993 826050 / Fax: +44 (0)1993 824411 / Email: [sales@jspsafety.com](mailto:sales@jspsafety.com) / Web: [www.jspsafety.com](http://www.jspsafety.com)

Do Not Publish without written permission from JSP Limited. Contact [copyright@jspsafety.com](mailto:copyright@jspsafety.com). Information correct in the United Kingdom at date of issue and may be subject to change. Any third-party machine and automated translations processed by users may have inaccuracies and should not be relied upon.

Page 1 of 2 / Issued 9 Aug 2025 / Copyright 2018 - 2025. JSP Limited. All Rights Reserved.



## SPECIFICATIONS

Material  
Aluminium Alloy

Gate Opening  
60mm

Product Weight  
243g

Connector Type  
Self Closing and Automatic Locking



Rated Weight / Load  
20kN Breaking Load



## DOWNLOADS

 [Image Pack \(ZIP\)](#)

 [doc-far0908.pdf \(PDF\)](#)



JSP Limited. Worsham Mill. Minster Lovell. Oxford OX29 0TA. England.

Tel: +44 (0)1993 826050 / Fax: +44 (0)1993 824411 / Email: [sales@jspsafety.com](mailto:sales@jspsafety.com) / Web: [www.jspsafety.com](http://www.jspsafety.com)

Do Not Publish without written permission from JSP Limited. Contact [copyright@jspsafety.com](mailto:copyright@jspsafety.com). Information correct in the United Kingdom at date of issue and may be subject to change. Any third-party machine and automated translations processed by users may have inaccuracies and should not be relied upon.

Page 2 of 2 / Issued 9 Aug 2025 / Copyright 2018 - 2025. JSP Limited. All Rights Reserved.

