

TECHNICAL SPECIFICATION



EVO®5 Olympus® Mid Peak Revolution® Wheel Ratchet Vented

White / AKF170-000-100



DESCRIPTION

The EVO®5 Olympus® safety helmet combines a super strong ABS shell designed for superior all day protection with the comfort benefits of the Evolution® 3D-Adjustment™ harness system.

EVO®5 Olympus® Industrial safety helmet passes all relevant industrial international standards.

OPTIONS

- Blue (AKF170-000-500)
- Green (AKF170-000-300)
- Grey (AKF170-000-400)
- Orange (AKF170-000-800)
- Red (AKF170-000-600)
- White (AKF170-000-100)**
- Yellow (AKF170-000-200)

SAFETY STANDARDS

EN 397 • CSA Z94.1



JSP Limited, Worsham Mill, Minster Lovell, Oxford OX29 0TA, England.























Tel: +44 (0)1993 826050 / Fax: +44 (0)1993 824411 / Email: sales@jsp-safety.com / Web: www.jsp-safety.com

Do Not Publish without written permission from JSP Limited. Contact copyright@jsp-safety.com. Information correct in the United Kingdom at date of issue and may be subject to change. Any third-party machine and automated translations processed by users may have inaccuracies and should not be relied upon.

Page 1 of 3 / Issued 23 Nov 2024 / Copyright 2018 - 2024, JSP Limited. All Rights Reserved.



SPECIFICATIONS


	Peak Mid		Impact Resistance 50 Joules
	Lateral Deformation Yes		Resistance to Molten Metals and Hot Solids Helmets (optional) Yes
	Maximum Temperature +50°C		Minimum Temperature -40°C
	ABS Shell Yes		Recyclable Shell
	Textile Harness		Depth Adjustment 3D Harness
	Wheel Ratchet Yes		Universal Accessories Slot Yes
	Ventilation Yes		Reflective Option Optional
	Integrated Eyewear Optional		ID card holder Optional
	BSI Kitemark Yes		Optional 2 point chinstrap (EN397 & EN 812 compliant) Optional
	Optional 4 point chinstrap (EN397 Compliant) Optional		JSPCheck Yes
	Product Weight 372g		Size 53-64cm

FEATURES



Tough ABS Shell

The EVO®5 safety helmet features an extremely robust ABS shell designed for superior protection. It features a distinctive five stripe design and the JSP Shield.



Textile Harness

A 6-point textile cradle harness system & Chamlon™ cotton sweatband offer unrivalled comfort.



CR2 Reflective

Using Class RA2, high intensity reflective. CR2 is the biggest step-up in night time visibility / reflectivity of head protection to date. Conforms to Class RA2, EN12899-1.



JSP Logo Express®

Strengthen your corporate identity by applying a company logo on a range of our safety helmets. Minimum order quantities and set-up charges apply.



Firmer Fit Available

The deep nape strap enables the firmest retention of any helmet, keeping it firmly rooted on the head. The Revolution® wheel ratchet makes it simple to tighten to the perfect fit.



3D Adjustment

The textile harness features unique 1-2-3 point depth settings. This offers the most precise fit attainable on an industrial safety helmet.



Accessories

A universal attachment slot enables firm fitting of a range of Surefit™ safety visors and ear defenders. EVOSpec® Integrated eyewear is also available.



Ventilation Option

Side and rear ventilation for optimum air movement inside the shell, reducing helmet temperatures by an average 2-3 degrees.

JSP Limited, Worsham Mill, Minster Lovell, Oxford OX29 0TA, England.

Tel: +44 (0)1993 826050 / Fax: +44 (0)1993 824411 / Email: sales@jspafety.com / Web: www.jspafety.com

Do Not Publish without written permission from JSP Limited. Contact copyright@jspafety.com. Information correct in the United Kingdom at date of issue and may be subject to change. Any third-party machine and automated translations processed by users may have inaccuracies and should not be relied upon.

Page 2 of 3 / Issued 23 Nov 2024 / Copyright 2018 - 2024, JSP Limited. All Rights Reserved.



APPLICATIONS

General guidance only and should not be considered a substitute for a full risk assessment

Construction and Infrastructure

Mining, Aggregates and Quarrying

Oil, Gas and Chemical Companies

Rail and Tunnelling

Renewable, Wind and Solar Energy

Utilities Contractors

LOGO

- Front
- Back
- Sides

RANGE



DOWNLOADS

-  [Image Pack \(ZIP\)](#)
-  [doc-invincible-evo5.pdf \(PDF\)](#)



JSP Limited, Worsham Mill, Minster Lovell, Oxford OX29 0TA, England.

Tel: +44 (0)1993 826050 / Fax: +44 (0)1993 824411 / Email: sales@jspsafety.com / Web: www.jspsafety.com

Do Not Publish without written permission from JSP Limited. Contact copyright@jspsafety.com. Information correct in the United Kingdom at date of issue and may be subject to change. Any third-party machine and automated translations processed by users may have inaccuracies and should not be relied upon.

Page 3 of 3 / Issued 23 Nov 2024 / Copyright 2018 - 2024. JSP Limited. All Rights Reserved.

