

TECHNICAL SPECIFICATION



FilterSpec® & FilterSpec® Pro Replacement Filters

FFP3 Valved Filters - Pk10 / ASG03B-101-100



DESCRIPTION

Replacement filters compatible with FilterSpec® and FilterSpec® Pro.

FilterSpec® and FilterSpec® Pro Replacement Filters meet the requirements of EN 149 when fitted to FilterSpec® or FilterSpec® Pro product.

OPTIONS

FFP2 Valved Filters - Pk10 (ASG02B-101-100)

FFP3 Valved Filters - Pk10 (ASG03B-101-100)



JSP Limited, Worsham Mill, Minster Lovell, Oxford OX29 0TA, England.

Tel: +44 (0)1993 826050 / Fax: +44 (0)1993 824411 / Email: sales@jsp-safety.com / Web: www.jsp-safety.com

Do Not Publish without written permission from JSP Limited. Contact copyright@jsp-safety.com. Information correct in the United Kingdom at date of issue and may be subject to change. Any third-party machine and automated translations processed by users may have inaccuracies and should not be relied upon.

Page 1 of 2 / Issued 22 May 2026 / Copyright 2018 - 2026. JSP Limited. All Rights Reserved.



SPECIFICATIONS

Face Fit Testing Required
Yes



Filter Type
P (Protects against solid and liquid aerosols)



Activated Carbon Layer
No

Maximum Total Inward Leakage (TIL)
2%

UK Assigned Protection Factor
20

Filter Shelf Life
5 years

Classification
FFP3 (Filtering Facepiece Particulate)

Usage
NR (Non-reusable)

Minimum Filtration Efficiency
99% for FFP3 Rated

Nominal Protection Factor
50



Exhalation Valve
Yes



Product Weight
13g

FEATURES




Integration

FilterSpec's unique design overcomes the problem of ill fitting masks, fogged lenses and non-conformity that can often occur when one item of PPE compromises another.



Quality Lens

The FilterSpec® Pro goggle features a 5.5 base curve lens. FilterSpec® lenses have a base curve of 6.5. Both offer optimal coverage and feature anti-mist and anti-scratch lens coatings.



Efficient Filter

The easily replaced filters are made from three layers for exceptional performance. Available with low resistance exhalation valve to reduce moisture and CO2 build-up.

RANGE



DOWNLOADS

[Image Pack \(ZIP\)](#)

[doc-filterspec-ffp3-mask.pdf \(PDF\)](#)



JSP Limited, Worsham Mill, Minster Lovell, Oxford OX29 0TA, England.

Tel: +44 (0)1993 826050 / Fax: +44 (0)1993 824411 / Email: sales@jgpsafety.com / Web: www.jgpsafety.com

Do Not Publish without written permission from JSP Limited. Contact copyright@jgpsafety.com. Information correct in the United Kingdom at date of issue and may be subject to change. Any third-party machine and automated translations processed by users may have inaccuracies and should not be relied upon.

Page 2 of 2 / Issued 22 May 2026 / Copyright 2018 - 2026. JSP Limited. All Rights Reserved.

