

EVO® ALTA™ Baseworker™ Vented

EVO® ALTA™ Baseworker™ (EN397) Vented Black Wheel Ratchet / ARB170-001-100



BESCHREIBUNG

The new EVO® ALTA™ offers all-round impact protection. The mountaineering-style helmet features a specialised shell structure and internal liner to increase durability and shock absorption performance. Precise adjustment settings enable a secure fit, ensuring the helmet remains stable. Engineered to maximise compatibility and accessory integration, EVO® ALTA™ is an adaptive system with built-in attachment points and an interchangeable front module.

EVO®ALTA™ Baseworker™ Vented meets the mandatory shock absorption and penetration resistance requirements of EN 12492 and is fully EN 397 compliant including an EN 397 compliant chinstrap. The 4-point chinstrap is designed to release under force if caught or snagged. EVO®ALTA™ Baseworker™ Vented meets the electrical insulation requirements of EN 50365:2002

OPTIONEN

EVO® ALTA™ Baseworker™ (EN397) Vented Black Wheel Ratchet (ARB170-001-100)

EVO® ALTA™ Baseworker™ (EN397) Vented Blue Wheel Ratchet Copy (ARB170-000-500)

EVO® ALTA™ Baseworker™ (EN397) Vented Extra Visibility Orange Wheel Ratchet (ARB170-001-600)

EVO® ALTA™ Baseworker™ (EN397) Vented Green Wheel Ratchet (ARB170-000-300)

EVO® ALTA™ Baseworker™ (EN397) Vented Red Wheel Ratchet Copy (ARB170-001-100)

EVO® ALTA™ Baseworker™ (EN397) Vented Wheel Ratchet (ARB170-000-100)

()























EVO® ALTA™ Baseworker™ (EN397) Vented High Visibility Yellow Wheel Ratchet (ARB170-00C-700)

SICHERHEITSTANDARDS

EN 397 • EN 50365



SPEZIFIKATIONEN

	Schirm Mikro		Stoßfestigkeit 100 Joules
	Seitliche Schlagfestigkeit 25 Joules		Schmelzmetall Ja
	Seitliche Verformung Ja		EN 50365 ELEKTRISCHE ISOLIERUNG 1000V
	Max. Temperatur +50°C		Min. Temperatur -40°C
	ABS-Schale Ja		EPP-Aufprall Absorber Ja
	Wiederverwendbar Schale		Textil Innenausstattung
	Belüftung Ja		Tiefeneinstellung 3D-Anpassung
	Drehradverschluss Ja		Fitted 4 point chinstrap (EN397 Compliant) Ausgestattet
	Universeller Zubehör-Steckplatz Ja		Reflektierendes CR2 Optional
	ID-Ausweishalter Optional		JSPCheck Ja
	Produktgewicht 500g		Größe 53-64cm

EIGENSCHAFTEN



All-Round Protection

EVO® ALTA™ provides all-round impact protection with top, side, front and rear shock absorption performance. The helmet is designed with an extended nape section to offer greater neck coverage.




Interchangeable Front Module

EVO® ALTA™ features a unique interchangeable front module. Select the integrated ID card holder for on-site identification or choose the logo-ready standard front to apply company branding. Both front modules enable attachment of a helmet lamp and other accessories.



Compatibility & Accessories

The EVO® ALTA™ range maximises compatibility and accessory integration. Attachment points on the front, sides and rear of the helmet shell enable firm fitting of ear defenders, faceshields, goggle and lamp straps, plus a range of other accessories.



EPP Liner

EVO® ALTA™ features an internal impact liner to increase shock absorption and penetration protection. Manufactured in expanded polypropylene (EPP), the liner is lightweight and ventilated for comfort.



Maximum Comfort

The Revolution® Flex wheel ratchet harness secures the helmet, eliminating pressure points to provide maximum comfort. Fitted with a replaceable Chamlon™ cotton sweatband and fully compatible with EVO® cooling sweatbands for protection against heat stress.



Secure Fit

The harness cradles the head to keep the helmet stable with an adjustable 4-point chinstrap for increased security. 3D-Adjustment depth settings enable the most precise fit attainable on a safety helmet.

JSP Limited, Worsham Mill, Minster Lovell, Oxford OX29 0TA, England.

Tel: +44 (0)1993 826050 / Fax: +44 (0)1993 824411 / Email: sales@jgpsafety.com / Web: www.jgpsafety.com

Do Not Publish without written permission from JSP Limited. Contact copyright@jgpsafety.com. Information correct in the United Kingdom at date of issue and may be subject to change. Any third-party machine and automated translations processed by users may have inaccuracies and should not be relied upon.

Page 2 of 3 / Issued 31 May 2026 / Copyright 2018 - 2026. JSP Limited. All Rights Reserved.





4-Point Chinstrap

The 4-point chinstrap is easy to adjust on the head. Size and anchorage point adjustment enable a tailored fit for different head sizes, ensuring stability and greater comfort.



Dual Ventilation

Side and rear ventilation in the helmet's shell and liner reduce temperatures by an average 2-3 degrees.



Custom Branding

Helmets can be customised to meet a corporate identity. Logo printing is available for the standard front module, helping to increase brand recognition and discourage theft. MOQs apply.

LOGO

- Vorderseite
- Beidseitig

SERIE



DOWNLOADS

-  [Bilderordner \(ZIP\)](#)



JSP Limited, Worsham Mill, Minster Lovell, Oxford OX29 0TA, England.

Tel: +44 (0)1993 826050 / Fax: +44 (0)1993 824411 / Email: sales@jspsafety.com / Web: www.jspsafety.com

Do Not Publish without written permission from JSP Limited. Contact copyright@jspsafety.com. Information correct in the United Kingdom at date of issue and may be subject to change. Any third-party machine and automated translations processed by users may have inaccuracies and should not be relied upon.

Page 3 of 3 / Issued 31 May 2026 / Copyright 2018 - 2026. JSP Limited. All Rights Reserved.

