

# Stealth<sup>™</sup> 8000

Clear Anti-mist / Anti-scratch Lens / ASA790-151-300



### DESCRIPTION

A lightweight safety spectacle, weighing just 26g, the wraparound 9 base curve polycarbonate lens has a built in adjustable PVC nosepiece for added comfort and stability. Low profile tension control temples provide extra grip. Temple tips feature spectacle cord attachment points. UVA, UVB and UVC protection.

# OPTIONS

Amber K Rated (ASA790-161-200) **Clear Anti-mist / Anti-scratch Lens (ASA790-151-300)** Clear K & N AS/AF Rated (ASA790-1A1-300) Clear K Rated (ASA790-161-300) Indoor/Outdoor Anti Scratch HC Lens (ASA790-162-900) LED Clear Anti-mist Lens (ASA106-121-300) Smoke K Rated (ASA790-166-400)

# SAFETY STANDARDS

EN 166



JSP Limited. Worsham Mill. Minster Lovell. Oxford OX29 0TA. England.

Tel: +44 (0)1993 826050 / Fax: +44 (0)1993 824411 / Email: sales@jspsafety.com / Web: www.jspsafety.com

Do Not Publish without written permission from JSP Limited. Contact copyright@jspsafety.com. Information correct in the United Kingdom at date of issue and may be subject to change. Any third-party machine and automated translations processed by users may have inaccuracies and should not be relied upon.



#### SPECIFICATIONS



Product Weight 26g



LIGHT TRANSMISSION BREAKDOWN Lens Shade number 1.2



Optical Class (1 – Class 1 – High quality for regular use. 2 – Class 2 – Medium quality for occasional use. 3 – Class 3 – Low quality for exceptional use) 1



The letter T, immediately after the mechanical strength symbol, authorises use for high speed particles at extreme temperatures. (-5°C and +55°C) Optional T

# FEATURES



# Comfort & Grip

Built-in soft rubber provides both comfort and grip to the side of the head to keep them secure without irritation.



### Spectacle Cord Anchor

The temple tips have a spectacle cord anchor point for further practicality, preventing loss or scratching from being put on rough surfaces.

# RANGE





RADIATION PROTECTION BREAKDOWN filtering effect Scale Number 2C



Manufacturer's Trademark JSP Dagger



Low Energy Impact resists a 6 mm, 0.86g ball @ 45 m/s  $^\circ$  Maximum protection for glasses  ${\rm F}$ 



### **Comfortable Nose Bridge**

Built-in adjustable PVC nose piece for added comfort and stability. It flexes and adjusts to fit the shape of the nose.

### DOWNLOADS

- Image Pack (ZIP)
- doc-stealth-8000-spectacles.pdf (PDF)



JSP Limited. Worsham Mill. Minster Lovell. Oxford OX29 0TA. England.

Tel: +44 (0)1993 826050 / Fax: +44 (0)1993 824411 / Email: sales@jspsafety.com / Web: www.jspsafety.com

Do Not Publish without written permission from JSP Limited. Contact copyright@jspsafety.com. Information correct in the United Kingdom at date of issue and may be subject to change. Any third-party machine and automated translations processed by users may have inaccuracies and should not be relied upon.

