

TECHNICAL SPECIFICATION



Single Tool Lanyard

Single Tool Lanyard / FAR0502



DESCRIPTION

Convenient stretch lanyard for tool holding, made from highly visible 16mm tubular webbing. Max 10kg.

OPTIONS

Single Tool Lanyard (FAR0502)



JSP Limited, Worsham Mill, Minster Lovell, Oxford OX29 0TA, England.

Tel: +44 (0)1993 826050 / Fax: +44 (0)1993 824411 / Email: sales@jsp-safety.com / Web: www.jsp-safety.com

Do Not Publish without written permission from JSP Limited. Contact copyright@jsp-safety.com. Information correct in the United Kingdom at date of issue and may be subject to change. Any third-party machine and automated translations processed by users may have inaccuracies and should not be relied upon.

Page 1 of 2 / Issued 31 May 2026 / Copyright 2018 - 2026. JSP Limited. All Rights Reserved.



SPECIFICATIONS

Length
0.85m to 1.35m



Rated Weight / Load
10kg (Tools)

Material
Highly Visible 16mm Tubular Elasticated Webbing

Delivered With
Lightweight Connector For Attachment To The
User's Belt

DOWNLOADS

 [Image Pack \(ZIP\)](#)



JSP Limited, Worsham Mill, Minster Lovell, Oxford OX29 0TA, England.

Tel: +44 (0)1993 826050 / Fax: +44 (0)1993 824411 / Email: sales@jspsafety.com / Web: www.jspsafety.com

Do Not Publish without written permission from JSP Limited. Contact copyright@jspsafety.com. Information correct in the United Kingdom at date of issue and may be subject to change. Any third-party machine and automated translations processed by users may have inaccuracies and should not be relied upon.

Page 2 of 2 / Issued 31 May 2026 / Copyright 2018 - 2026. JSP Limited. All Rights Reserved.

