

## AFP-25 Helmet Mounted Faceshield

AFP-25 Helmet Mounted Faceshield with weight balancing system / AFF132-440-408



### DESCRIPTION

The AFP-25 has been designed to provide the ultimate in industrial-grade arc flash eye and face protection. In collaboration with arc risk specialist manufacturers Oberon, the faceshield has been tested and rated on the JSP EVO® helmet range (excluding Evo 6100 Full Brim), achieving GS-ET-29 arc class 2 and maximum permissible ATPV rating of 25cal/cm<sup>2</sup> under ASTM F2178. Simple to fit to new or existing EVO® range helmets, with an optional weight balance system available (compatible with EVO®5 helmet only) to facilitate one-handed stowing for improved working clearance.

### OPTIONS

AFP-25 Helmet Mounted Faceshield (AFF122-440-408)

**AFP-25 Helmet Mounted Faceshield with weight balancing system (AFF132-440-408)**

### SAFETY STANDARDS

EN 166 • EN 170 • ANSI Z87. 1 • GS-ET-29 • ASTM F2178-12



## SPECIFICATIONS



**RADIATION PROTECTION BREAKDOWN** filtering effect  
Scale Number  
2C



**LIGHT TRANSMISSION BREAKDOWN** Lens Shade number  
2



Manufacturer's Trademark  
**JSP Dagger / Oberon Company Logo**



Medium Energy Impact resists a 6 mm, 0.86g ball @ 120 m/s Maximum protection for goggles.  
**B**



Optical Class (1 – Class 1 – High quality for regular use. 2 – Class 2 – Medium quality for occasional use. 3 – Class 3 – Low quality for exceptional use)  
**1**



Protection Against Short Circuit Electric Arc  
**8**



Resistance to Surface Damage by Fine Particles (optional)  
**K**



Resistance to fogging (optional)  
**Yes, But not to "N"**



Visor Length  
**340mm**



Recyclable  
**Yes**



Material  
**Polycarbonate Visor**

Material  
**Polyethylene (WBS) Weight Balance System Side Arms**

Product Weight  
**497G**

## FEATURES



### Weight Balancing System

Weight balancing system variant allows secure stowing of the visor for safe and convenient working. The system supports one-handed operation, allowing the visor to be quickly lifted and locked in place above the helmet crown for maximum working clearance. Compatible with EVO®5 only

## DOWNLOADS

[Image Pack \(ZIP\)](#)

[doc-afp-25-arc-faceshield.pdf \(PDF\)](#)



JSP Limited, Worsham Mill, Minster Lovell, Oxford OX29 0TA, England.

Tel: +44 (0)1993 826050 / Fax: +44 (0)1993 824411 / Email: [sales@jspsafety.com](mailto:sales@jspsafety.com) / Web: [www.jspsafety.com](http://www.jspsafety.com)

Do Not Publish without written permission from JSP Limited. Contact [copyright@jspsafety.com](mailto:copyright@jspsafety.com). Information correct in the United Kingdom at date of issue and may be subject to change. Any third-party machine and automated translations processed by users may have inaccuracies and should not be relied upon.

Page 2 of 2 / Issued 16 Jun 2025 / Copyright 2018 - 2025. JSP Limited. All Rights Reserved.

