

Trípode

Trípode / FAR1003



DESCRIPCIÓN

Trípode de espacio confinado con un sistema de polea para guiar el cable del cabrestante, si se usa. Adecuado para su uso en superficies irregulares, el ajuste es mediante el deslizamiento de las patas telescópicas (interior y exterior). Capacidad de carga 500kg.

OPCIONES

Trípode (FAR1003)

NORMAS DE SEGURIDAD

EN 795



ESPECIFICACIONES

Peso del producto
12150g

USOS

Sólo es una orientación general y no debe considerarse un sustituto de una evaluación de riesgos completa

Espacios Confinados

DESCARGAR

 [Colección de imágenes \(ZIP\)](#)

 [doc-far1003.pdf \(PDF\)](#)



JSP Limited, Worsham Mill, Minster Lovell, Oxford OX29 0TA, England.

Tel: +44 (0)1993 826050 / Fax: +44 (0)1993 824411 / Email: sales@jspsafety.com / Web: www.jspsafety.com

Do Not Publish without written permission from JSP Limited. Contact copyright@jspsafety.com. Information correct in the United Kingdom at date of issue and may be subject to change. Any third-party machine and automated translations processed by users may have inaccuracies and should not be relied upon.

Page 2 of 2 / Issued 25 Nov 2024 / Copyright 2018 - 2024. JSP Limited. All Rights Reserved.

