

TECHNICAL SPECIFICATION



Stealth™ Hybrid

Stealth™Hybrid replacement smoke lens (KN) / ASB450-0A3-000



DESCRIPTION

Functions as either a safety spectacle or a safety goggle once the arms have been disconnected and the strap has been attached. Supplied with goggle strap and a set of spectacle arms.

OPTIONS

- Stealth™ Hybrid (ASA450-151-102)
- Stealth™Hybrid replacement clear lens (KN) (ASB450-051-300)
- Stealth™Hybrid replacement smoke lens (KN) (ASB450-0A3-000)**

SAFETY STANDARDS

EN 166 • EN 170



JSP Limited, Worsham Mill, Minster Lovell, Oxford OX29 0TA, England.

Tel: +44 (0)1993 826050 / Fax: +44 (0)1993 824411 / Email: sales@jsspsafety.com / Web: www.jsspsafety.com

Do Not Publish without written permission from JSP Limited. Contact copyright@jsspsafety.com. Information correct in the United Kingdom at date of issue and may be subject to change. Any third-party machine and automated translations processed by users may have inaccuracies and should not be relied upon.

Page 1 of 2 / Issued 2 Oct 2023 / Copyright 2018 - 2023. JSP Limited. All Rights Reserved.



SPECIFICATIONS



RADIATION PROTECTION BREAKDOWN filtering effect
Scale Number
2C



LIGHT TRANSMISSION BREAKDOWN Lens Shade number
1.2



Optical Class (1 – Class 1 – High quality for regular use. 2 – Class 2 – Medium quality for occasional use. 3 – Class 3 – Low quality for exceptional use)
1



Medium Energy Impact resists a 6 mm, 0.86g ball @ 120 m/s Maximum protection for goggles.
B - When Fitted With Goggle Strap



Low Energy Impact resists a 6 mm, 0.86g ball @ 45 m/s °
Maximum protection for glasses
F - When Fitted With Side Arms



Resistance to Surface Damage by Fine Particles (optional)
K



Resistance to fogging (optional)
N

FEATURES



Adjustable Arms

Spectacle arms can be clipped into the frame to create the safety spectacle. Pantoscopic angle adjustment allows the frame to be angled to offer a customised fit.



EVA Foam Seal

EVA foam provides comfort on the bridge of the nose and around the eyes whilst providing ventilation.



Changeable Lens

The changeable lens allows users to replace the lens according to different applications.

RANGE

**STEALTH
HYBRID**

DOWNLOADS

[Image Pack \(ZIP\)](#)

[doc-stealth-hybrid.pdf \(PDF\)](#)



JSP Limited, Worsham Mill, Minster Lovell, Oxford OX29 0TA, England.

Tel: +44 (0)1993 826050 / Fax: +44 (0)1993 824411 / Email: sales@jspsafety.com / Web: www.jspsafety.com

Do Not Publish without written permission from JSP Limited. Contact copyright@jspsafety.com. Information correct in the United Kingdom at date of issue and may be subject to change. Any third-party machine and automated translations processed by users may have inaccuracies and should not be relied upon.

Page 2 of 2 / Issued 2 Oct 2023 / Copyright 2018 - 2023. JSP Limited. All Rights Reserved.

