TECHNICAL SPECIFICATION



EVO®2 Badge Vented Slip Ratchet

EVO®2 Badge Vented Slip Ratchet Blue / APB030-000-500



DESCRIPTION

EVO®2 Badge provides a simple solution for identification on site, combining the established EVO®2 with the JSP badge and ID card holder. The sturdy helmet features a built-in next generation badge holder with lamp bracket, that slots seamlessly into a purpose-engineered shell recess.

OPTIONS

EVO®2 Badge Vented Slip Ratchet Blue (APB030-000-500)

EVO®2 Badge Vented Slip Ratchet White (APB030-000-100) EVO®2 Badge Vented Slip Ratchet Yellow (APB030-000-200)

SAFETY STANDARDS

EN 397















SPECIFICATIONS



Peak Mid



Resistance to Molten Metals and Hot Solids (optional)



Minimum Temperature





Recyclable Shell



Depth Adjustment 3D Harness



Universal Accessories Slot

Yes



BSI Kitemark

Yes



Optional 4 point chinstrap (EN397 Compliant)

Optional



ID card holder

Fitted



Product Weight

435g



Impact Resistance

50 Joules



Maximum Temperature

+50°C



HDPE Shell

Yes



LDPE Harness

Yes



Slip Ratchet Slip



•





Reflective Option

Optional



Optional 2 point chinstrap (EN397 & EN 812 compliant)

Optional



JSPCheck

Yes



Size 53-64cm

FEATURES



Firmest Fit Available

The deep nape strap enables the firmest retention of any helmet, keeping it firmly rooted on the head. The OneTouch™ slip ratchet makes it simple to tighten to the perfect fit.



CR2 Reflective

Using Class RA2, high intensity reflective. CR2 is the biggest step-up in night time visibility/reflectivity of head protection to date. Conforms to Class RA2, EN12899-1.



Supreme Comfort

A traditional 6-point polyethylene harness making the EVO®2 the more economical choice, whilst still providing the same high performance as the EVO®3.



ID Card Holder

Clear acrylic badge holder, using simple push and slide system to fit and replace standard business card size identification. A lamp bracket is positioned at the top of the unit.



3D Adjustment

The polyethylene harness features unique 1-2-3 point depth settings. This offers the most precise fit attainable on an industrial safety helmet.



Accessories

Universal attachment slot enables firm fitting of a range of safety visors and ear defenders.



JSP Logo Express®

Strengthen your corporate identity by applying a company logo on a range of our safety helmets. Minimum order quantities and set-up charges apply.



Accessories

Wide range of compatible and certified accessories available, with the EVOGuard® faceshield range and the Sonis® helmet-mounted ear defenders. Also available is a comprehensive range of thermal liners, UV capes, and chinstraps.





JSP Limited. Worsham Mill. Minster Lovell. Oxford OX29 0TA. England.

Tel: +44 (0)1993 826050 / Fax: +44 (0)1993 824411 / Email: sales@jspsafety.com / Web: www.jspsafety.com

Do Not Publish without written permission from JSP Limited. Contact copyright@jspsafety.com. Information correct in the United Kingdom at date of issue and may be subject to change. Any third-party machine and automated translations processed by users may have inaccuracies and should not be relied upon.







Ventilation

Vented shell to increase comfort and allow cooling air flow, reducing helmet temperatures by an average 2-3 degrees Celsius. Non-vented version available with electrical insulation properties.



Tough HDPE Shell

In tests the EVO®2 proved far tougher than the EN397 standard required and far tougher than any of its competitors.



CR2 Reflectivity

CR2 reflective decals available as an optional accessory, offering, on average, 60% higher reflectivity than standard reflective clothing. CR2 is optional.



Secure Fit

Featuring easy to use OneTouch® slip ratchet, 3D adjustable harness, and replaceable Chamlon $^{\mbox{\tiny TM}}$ sweatband for a secure, comfortable fit. Range of replacement sweatbands available.

LOGO

✓ Sides



RANGE



DOWNLOADS

Image Pack (ZIP)

doc-invincible-evo2.pdf (PDF)











