# TECHNICAL SPECIFICATION



## K2™ 2m Twin Fall Arrest Lanyard

K2™ 2m Twin Fall Arrest Lanyard / FAR0405



### DESCRIPTION

The  $K2^{TM}$  internal fall arrest lanyards come with the energy absorption feature incorporated within their core. Without the need for an extra energy absorption pack, they are lighter in weight than other solutions, and also prevent trip hazards.

The elastic nature of these lanyards reduce the actual effective length of the lanyard, and it is therefore important to note both lanyard length and effective length.

#### OPTIONS

K2™ 2m Twin Fall Arrest Lanyard (FAR0405)

#### SAFETY STANDARDS

EN 355















#### **SPECIFICATIONS**

Fall Indicator

No

Material

40mm Wide Tubular Polyester Webbing With Textile Loops

Sharp Edge

No

Protective Rope Sleeve

No

**Delivered With** 

1 Quarter Turn Aluminium Connector. Gate Opening: 21mm. Conforms To EN362:2004 Class B. 2 Aluminium Scaffold Hooks. Gate Opening 60mm. Conforms To EN362 Class A/T. Length 1.4m To 2m

Shock Absorber

Internal

Rope Ends

Х



Product Weight

1780g

#### DOWNLOADS





doc-far0404-far0405.pdf (PDF)













