TECHNICAL SPECIFICATION



Spartan™ 2m Adjustable Work Positioning Lanyard

Spartan™ 2m Adjustable Work Positioning Lanyard / FAR0308



DESCRIPTION

Work positioning and restraint lanyard, adjustable up to 2m, made from 14mm polyamide 3-strand rope (complying with ISO 1140).

OPTIONS

Spartan[™] 2m Adjustable Work Positioning Lanyard (FAR0308)

SAFETY STANDARDS

EN 358











SPECIFICATIONS

Length 2m Max.

Rope Ends

Stitched and Covered With Polyethylene Protective Sleeve. Abrasion Resistant Thimbles Provided Within Loops

Adjustment Device

Manual Ring Type Adjuster Of Forged Alloy Steel

Delivered With

2 Screw Gate Connectors In Alloy Steel. Gate Opening 18mm. Conforms To EN362 Class B & M.

Material

14mm Polyamide 3 Strand Twisted Rope (Complying To ISO 1140). Black and Red Tracer In The Rope To Indicate Degradation of Material.

Protective Rope Sleeve

No



Product Weight

770g

APPLICATIONS

General guidance only and should not be considered a substitute for a full risk assessment

MEWP Window Cleaning

DOWNLOADS

Image Pack (ZIP)















