ESPECIFICACIONES TÉCNICAS

Spartan™ Cordaje de posicionamiento de trabajo ajustable 2m

Spartan™ Cordaje de posicionamiento de trabajo ajustable 2m / FAR0308



DESCRIPCIÓN

Cordaje de retención y posicionamiento de trabajo, ajustable hasta 2m, fabricado con cuerda de poliamida de 14mm de 3 hilos (conforme a ISO 1140).

OPCIONES

Spartan™ Cordaje de posicionamiento de trabajo ajustable 2m (FAR0308)

NORMAS DE SEGURIDAD

EN 358

JSP Limited. Worsham Mill. Minster Lovell. Oxford OX29 0TA. England.

Tel: +44 (0)1993 826050 / Fax: +44 (0)1993 824411 / Email: sales@jspsafety.com / Web: www.jspsafety.com

Do Not Publish without written permission from JSP Limited. Contact copyright@jspsafety.com. Information correct in the United Kingdom at date of issue and may be subject to change. Any third-party machine and automated translations processed by users may have inaccuracies and should not be relied upon.

ESPECIFICACIONES

Longitud
2m max.

Extremos de cuerda
Costuras protegidas mediante una funda protectora de polietileno. Guardacabos resistentes a la abrasión integrados en los bucles.

Dispositivo de ajuste
Regulador manual de anilla de acero aleado forjado

Se entrega con
2 conectores de puerta de tornillo de acero aleado. Apertura del gatillo: 18 mm. Cumple con EN362 Clase B y M.

Material
Cuerda de poliamida de 14 mm de diámetro, 3 cordones trenzados (conforme a ISO 1140). Trazador negro y rojo en la cuerda para indicar la degradación del material.

Manga protectora de cuerda

Peso del producto
770g

DESCARGAR

Colección de imágenes (ZIP)
doc-far0308-far0312.pdf (PDF)

JSP Limited. Worsham Mill. Minster Lovell. Oxford OX29 0TA. England.

Tel: +44 (0)1993 826050 / Fax: +44 (0)1993 824411 / Email: sales@jspsafety.com / Web: www.jspsafety.com

Do Not Publish without written permission from JSP Limited. Contact copyright@jspsafety.com. Information correct in the United Kingdom at date of issue and may be subject to change. Any third-party machine and automated translations processed by users may have inaccuracies and should not be relied upon.