TECHNICAL SPECIFICATION



Replacement Helmet for Powercap® Infinity®

Black / AKG179-P01-100



DESCRIPTION

Replacement helmet for the PowerCap® Infinity®. The head protection element of the PowerCap® Infinity® is based on the EVO®5 Olympus® industrial safety helmet. The helmet combines a super strong ABS shell designed for superior all day protection with the comfort benefits of the Evolution® 3D-Adjustment™ harness system.

*Other colours available on request. Minimum order quantities apply.

OPTIONS

Black (AKG179-P01-100)

Blue (AKG179-P00-500) White (AKG179-P00-100)


SAFETY STANDARDS

EN 397















SPECIFICATIONS

Helmet



Impact Resistance 50 Joules



Resistance to Molten Metals and Hot Solids (optional)





Minimum Temperature





Recyclable Shell



Depth Adjustment 3D Harness



Ventilation No



BSI Kitemark





JSPCheck Yes



Peak Micro



Lateral Deformation Yes



Maximum Temperature



+50°C



ABS Shell Yes



Textile



Harness



Slip Ratchet Wheel



Reflective Option

Fitted



Optional 4 point chinstrap (EN397 Compliant)

Optional



Product Weight

415g

FEATURES



Powerful Twin Turbo Performance

The patented Twin Turbo Technology controls the airflow through the headtop to maximise user comfort and optimise energy efficiency. Real time diagnostics ensure that the twin impeller motor unit delivers the optimum level of airflow depending on the wearer's demands and regulates the intake and internal pressure delivering a minimum of 160 litres a minute of filtered clean air.



No need to FACE FIT test

PowerCap® Infinity® removes the need for fit testing, ensuring that a high volume of clean air is delivered to the breathing zone giving a high level of protection.



Smart PPE

Real time diagnostics monitor the system and the wearer twice per second, giving the user accurate, dynamic feedback. Periods of high respiratory demand are monitored and catered for by constantly maintaining a positive pressure inside the respirator. Feedback is given on battery and filter condition via the heads up display and audible notifications.



Head Protection

PowerCap® Infinity® is built around the super strong ABS shell of the EVO®5 Olympus® industrial safety helmet. Fitted with the Revolution® Flex wheel ratchet harness, the helmet is designed to reduce pressure for the perfect fit and all-day comfort.



High Efficiency Filters

The high capacity HEPA filters coupled with the aerodynamically optimised pre-filter covers ensure that PowerCap® Infinity® delivers 160 litres per minute of clean air to the user with maximum battery efficiency. Filters can be effortlessly replaced using an intuitive quick-change bayonet system.



Panaromic Impact Visor

The optical class 1 visor conforms to EN166.B offering impact protection at speeds of up to 270 mph (tested using a 6mm steel ball bearing). The visor has a replaceable peel-off visor protector to prolong its life.





JSP Limited. Worsham Mill. Minster Lovell. Oxford OX29 0TA. England

Tel: +44 (0)1993 826050 / Fax: +44 (0)1993 824411 / Email: sales@jspsafety.com / Web: www.jspsafety.com

Do Not Publish without written permission from JSP Limited. Contact copyright@jspsafety.com. Information correct in the United Kingdom at date of issue and may be subject to change. Any third-party machine and automated translations processed by users may have inaccuracies and should not be relied upon.







Ear Defenders

The PowerCap® Infinity® has been developed to seamlessly integrate with the optional Sonis® helmet mounted ear defenders. Designed by the JSP R&D team and working with a leading UK acoustic engineering research facility, the Sonis® helmet mounted range includes an SNR 26, while the Sonis Compact has an SNR of 31 and then peaks at an unbeaten SNR 36dB. The helmet adaptor and the cushion surface area work together to provide optimum cushion pressure and comfort.



Tested to the MAX

Hundreds of hours of human treadmill tests were conducted in a purpose built salt dust challenge chamber to optimise mass, balance and sealing elements. Extensive user trials were conducted, putting the PowerCap® Infinity® to the test in a variety of harsh conditions.



Perfect Fit to Combat Dust

Dust in the workplace is a significant issue. The latest HSE figures (2017) show that 18,000 new cases of work-related respiratory disease were diagnosed. A significant proportion of these were the result of exposure to silica. While the problem is widely acknowledged and use of respiratory equipment is high, it is often not suitable for the person or the environment it is being used in.



Minimal Maintenance

PowerCap® Infinity® has been developed as a modular system, making it easy to disassemble and reassemble for ease of cleaning and maintenance. To ensure the optimal performance of PowerCap® Infinity® it is important that maintenance is carried out on a regular basis. No specialist tools required.



Tough ABS Shell

The EVO®5 safety helmet features an extremely robust ABS shell designed for superior protection. It features a distinctive five stripe design and the JSP Shield.



Firmest Fit Available

The deep nape strap enables the firmest retention of any helmet, keeping it firmly rooted on the head. The Revolution® wheel ratchet makes it simple to tighten to the perfect fit.



Textile Harness

A 6 point terylene cradle harness system & Egyptian cotton Chamlon™ sweatband offers unrivalled comfort.



3D Adjustment

The textile harness features unique 1-2-3 point depth settings. This offers the most precise fit attainable on an industrial safety helmet.



CR2 Reflective

Using Class RA2, high intensity reflective. CR2 is the biggest step-up in night time visibility / reflectivity of head protection to date. Conforms to Class RA2, EN12899-1.

RANGE VIDEOS



youtu.be/jS1Fr-xVS1I

- youtu.be/IMJIVCKiTdo
- youtu.be/u7dUKX-_vAc

DOWNLOADS

Image Pack (ZIP)

doc-powercap_infinity.pdf (PDF)









