

ESPECIFICACIONES TÉCNICAS



Swiss One EXPLORER 2

1EXP2GEN23YKN / 1EXP2GEN23YKN



DESCRIPCIÓN

The new generation of Hybrid range..., explorer Generation 2 offers a total comfort thanks to its amazing wrap-around frame. With a waterproof foam and innovative system to swap temples with a strap! With the strap, EXPLORER 2 provides exceptional protection against sprays of solids and liquids, and against dust. This item is also available in the RX range and with the strap it becomes a spectacle in the Ballistic range.

OPCIONES

1EXP2GEN23CKN (1EXP2GEN23CKN)
1EXP2GEN23YKN (1EXP2GEN23YKN)
1EXPE2GEN23SKN (1EXPE2GEN23SKN)

NORMAS DE SEGURIDAD

EN 170 • EN 166



JSP Limited, Worsham Mill, Minster Lovell, Oxford OX29 0TA, England.












Tel: +44 (0)1993 826050 / Fax: +44 (0)1993 824411 / Email: sales@jgpsafety.com / Web: www.jgpsafety.com

Do Not Publish without written permission from JSP Limited. Contact copyright@jgpsafety.com. Information correct in the United Kingdom at date of issue and may be subject to change. Any third-party machine and automated translations processed by users may have inaccuracies and should not be relied upon.









Page 1 of 2 / Issued 13 Jun 2026 / Copyright 2018 - 2026. JSP Limited. All Rights Reserved.



ESPECIFICACIONES

 <p>PROTECCIÓN RADIOLÓGICA Valor de escala de efecto de filtrado 2</p>	 <p>TRANSMISIÓN DE LA LUZ Valor de oscurecimiento de lente 1.2</p>
 <p>Marca del fabricante Swiss One Swiss One</p>	 <p>Clase óptica (1- Clase 1- alta calidad para uso regular. 2 - Clase 2 - calidad media para uso ocasional. 3 - Clase 3- calidad baja para un uso excepcional). 1</p>
 <p>El impacto de baja energía resiste una bola de 6 mm, 0,86 g a 45 m/s de Máxima protección para gafas F - Cuando se instalan las patillas laterales</p>	 <p>Impacto de energía media resiste una bola de 6 mm, 0,86 g a 120 m/s Máxima protección para gafas panorámicas. B - Cuando se coloca la cinta elástica</p>
 <p>La letra T, inmediatamente después del símbolo de resistencia mecánica, autoriza el uso de partículas de alta velocidad a temperaturas extremas. (-5° y +55°c) opcional T</p>	 <p>Resistencia al daño superficial por partículas finas (opcional) K</p>
 <p>Resistencia al empañamiento (opcional) N</p>	<p>Revestimiento Excellence (KN Anti-Rayado/Anti-Niebla) Sí</p>
 <p>Curva de la base de la lente 8</p>	<p>Puente nasal blando Sí</p>
<p>Puntas blandas - Templo plano flexible sin presión Sí</p>	<p>Brazos laterales giratorios Sí</p>
<p>Inserto RX Inserto RX opcional (4EXPLINSERT)</p>	 <p>Peso del producto 38/45g</p>

CARACTERÍSTICAS

 <p>Anti-mist Anti-mist</p>	 <p>Anti-scratch Anti-scratch</p>
 <p>Soft Nose Pad Soft nose pad</p>	 <p>Rotating Arms Rotating arms</p>
 <p>Lens Curve Lens curve</p>	 <p>Soft End Tips Soft end tips</p>
 <p>High Performance Coating Anti-scratch / anti-fog high performance coating</p>	 <p>RX Insert Compatible RX Insert compatible</p>

GAMA



DESCARGAR

-  [Colección de imágenes \(ZIP\)](#)
-  [doc-ce-explorer-2-spectacles.pdf \(PDF\)](#)
-  [doc-ukca-explorer-2-spectacles.pdf \(PDF\)](#)
-  [doc-ukca-explorer-2-goggles.pdf \(PDF\)](#)
-  [doc-ce-explorer-2-goggles.pdf \(PDF\)](#)



JSP Limited, Worsham Mill, Minster Lovell, Oxford OX29 0TA, England.

Tel: +44 (0)1993 826050 / Fax: +44 (0)1993 824411 / Email: sales@jspsafety.com / Web: www.jspsafety.com

Do Not Publish without written permission from JSP Limited. Contact copyright@jspsafety.com. Information correct in the United Kingdom at date of issue and may be subject to change. Any third-party machine and automated translations processed by users may have inaccuracies and should not be relied upon.

Page 2 of 2 / Issued 13 Jun 2026 / Copyright 2018 - 2026. JSP Limited. All Rights Reserved.

