

TECHNICAL SPECIFICATION



Aluminium Twist Lock Karabiner

Aluminium Twist Lock Karabiner / FAR0905



DESCRIPTION

Aluminium self-closing & automatic locking type connector. Breaking load 23kN.

OPTIONS

Aluminium Twist Lock Karabiner (FAR0905)

SAFETY STANDARDS

EN 362



JSP Limited, Worsham Mill, Minster Lovell, Oxford OX29 0TA, England.

Tel: +44 (0)1993 826050 / Fax: +44 (0)1993 824411 / Email: sales@jspsafety.com / Web: www.jspsafety.com

Do Not Publish without written permission from JSP Limited. Contact copyright@jspsafety.com. Information correct in the United Kingdom at date of issue and may be subject to change. Any third-party machine and automated translations processed by users may have inaccuracies and should not be relied upon.

Page 1 of 2 / Issued 11 Oct 2024 / Copyright 2018 - 2024. JSP Limited. All Rights Reserved.



SPECIFICATIONS

Material
Aluminium

Gate Opening
21mm



Product Weight
84g

Connector Type
Self Closing and Automatic Locking



Rated Weight / Load
23kN Breaking Load

DOWNLOADS

 [Image Pack \(ZIP\)](#)

 [doc-far0904-far0905-far0941.pdf \(PDF\)](#)



JSP Limited, Worsham Mill, Minster Lovell, Oxford OX29 0TA, England.

Tel: +44 (0)1993 826050 / Fax: +44 (0)1993 824411 / Email: sales@jspsafety.com / Web: www.jspsafety.com

Do Not Publish without written permission from JSP Limited. Contact copyright@jspsafety.com. Information correct in the United Kingdom at date of issue and may be subject to change. Any third-party machine and automated translations processed by users may have inaccuracies and should not be relied upon.

Page 2 of 2 / Issued 11 Oct 2024 / Copyright 2018 - 2024. JSP Limited. All Rights Reserved.

