

# TECHNICAL SPECIFICATION



## Swiss One COVERLITE

1COV23CKN / 1COV23CKN



### DESCRIPTION

COVERLITE one of the best definition of a Creative eyewear... overspecs for prescription wearers or spectacle for visitors whatever the way you wear it you will love it! With an unrestricted peripheral vision, high side arms graduate to soft, flexible material for additional comfort. Pantoscopic side arms adapt to any facial shape for customised fit and optimal protection with soft grip for a pressure free fit and a version available in Orange 550 lens for specific applications such as surface inspection, mechanical work, ultra-violet light, vulcanization, work with curing light lamp, dentist and medical application.

### OPTIONS

1COV23C (1COV23C)  
**1COV23CKN (1COV23CKN)**  
1COV23OR550 (1COV23OR550)  
1COV23S (1COV23S)  
1COV23SKN (1COV23SKN)  
1COV23W5 (1COV23W5)

### SAFETY STANDARDS

EN 170 • EN 166



JSP Limited, Worsham Mill, Minster Lovell, Oxford OX29 0TA, England.

Tel: +44 (0)1993 826050 / Fax: +44 (0)1993 824411 / Email: [sales@jspsafety.com](mailto:sales@jspsafety.com) / Web: [www.jspsafety.com](http://www.jspsafety.com)

Do Not Publish without written permission from JSP Limited. Contact [copyright@jspsafety.com](mailto:copyright@jspsafety.com). Information correct in the United Kingdom at date of issue and may be subject to change. Any third-party machine and automated translations processed by users may have inaccuracies and should not be relied upon.

Page 1 of 2 / Issued 29 Apr 2025 / Copyright 2018 - 2025. JSP Limited. All Rights Reserved.



## SPECIFICATIONS



LIGHT TRANSMISSION BREAKDOWN Lens Shade number  
5



Manufacture's Trademark Swiss One  
**Swiss One**



Low Energy Impact resists a 6 mm, 0.86g ball @ 45 m/s °  
Maximum protection for glasses  
**F**

Anti-Scratch/Anti-Fog Coating (23)  
**Yes**

Lightweight  
**Yes**

Soft End Tips - Flex Flat Temple Pressure Free  
**Yes**

Prescription Compatible  
**Yes**



Product Weight  
**35g**



LIGHT TRANSMISSION BREAKDOWN Lens Shade number  
2.5



Optical Class (1 – Class 1 – High quality for regular use. 2 –  
Class 2 – Medium quality for occasional use. 3 – Class 3 –  
Low quality for exceptional use)  
**1**



The letter T, immediately after the mechanical strength  
symbol, authorises use for high speed particles at extreme  
temperatures. (-5°C and +55°C) Optional  
**T**

Lens Base Curve  
**2.5**

Rotating Side Arms  
**Yes**

Metal Free (Di Electric)  
**Yes**

FLEXoFIT Technology  
**Yes**

## FEATURES



### Anti-mist

Anti-mist



### Lens Curve

Lens curve



### Lightweight

Lightweight



### Soft End Tips

Soft end tips



### Metal Free

Metal free



### Anti-scratch

Anti-scratch



### High Performance Coating

Anti-scratch / anti-fog high performance coating



### Rotating Arms

Rotating arms



### Soft Nose Pad

Soft nose pad



### Flexofit Technology

Flexofit technology

## RANGE



## DOWNLOADS



[Image Pack \(ZIP\)](#)



[doc-coverlite-updated-15.10.19.pdf \(PDF\)](#)



JSP Limited, Worsham Mill, Minster Lovell, Oxford OX29 0TA, England.

Tel: +44 (0)1993 826050 / Fax: +44 (0)1993 824411 / Email: [sales@jsp-safety.com](mailto:sales@jsp-safety.com) / Web: [www.jsp-safety.com](http://www.jsp-safety.com)

Do Not Publish without written permission from JSP Limited. Contact [copyright@jsp-safety.com](mailto:copyright@jsp-safety.com). Information correct in the United Kingdom at date of issue and may be subject to change. Any third-party machine and automated translations processed by users may have inaccuracies and should not be relied upon.

Page 2 of 2 / Issued 29 Apr 2025 / Copyright 2018 - 2025. JSP Limited. All Rights Reserved.

