TECHNICAL SPECIFICATION



Mk®7.0

MK®7.0 Long Peak Vented White Helmet - Wheel Ratchet / AHN170-000-100



DESCRIPTION

Mk®7.0 features classic shell design with rain channel. Available with three ventilation options and offering compatibility with EVO® accessories and a range of other JSP PPE, the Mk®7.0 provides the latest performance while retaining the styling of traditional industrial safety helmets.

OPTIONS

MK@7.0 Long Peak White Helmet - Wheel Ratchet (AHM170-000-100)

MK®7.0 Long Peak White Helmet - Wheel Ratchet - 3Pt Lamp Bracket + Cable Loop (AHM179-300-100)

MK®7.0 Long Peak Vented White Helmet - Wheel Ratchet (AHN170-000-100)

MK®7.0 Long Peak Vented White Helmet - Wheel Ratchet - Large Vents (AHO170-000-100)

*MK®7.0 Long Peak Vented White Helmet - Wheel Ratchet -Large Vents - LED Lamp Bracket + LED Lamp (AHO171-J00-100)

SAFETY STANDARDS

EN 50365 • EN 397















SPECIFICATIONS



Peak

Standard



Resistance to Molten Metals and Hot Solids (optional) Yes



Minimum Temperature

-40°C



Recyclable Yes



Depth Adjustment 3D Harness



Universal Accessories Slot

Yes



BSI Kitemark

Yes



Optional 4 point chinstrap (EN397 Compliant)
Optional



Product Weight 393g (Approx)



EN 50365 ELECTRICAL INSULATION

1000V



Impact Resistance 50 Joules



Maximum Temperature

+50°C



HDPE Shell

Yes



Textile Harness



Wheel Ratchet

Yes



Integrated Eyewear

Optional



Optional 2 point chinstrap (EN397 & EN 812 compliant)

Optional



JSPCheck

Yes



Size

53-64cm



Ventilation Small Vent

FEATURES



Strength And Comfort

The Mk®7.0 helmet features a super-strong HDPE shell combined with Revolution® wheel ratchet harness and Chamlon™ sweatband for maximum comfort and perfect fit.



Classic Design

The Mk®7.0 classic shell design features a rain channel around the brim, distinctive JSP shield, and raised 'stripe' on the crown.



Accessories

The Mk®7.0 is also compatible with EVO® helmet accessories, including thermal liners, neck capes, and chinstraps. Lamp brackets and cable loops are available as factory-fitted options.



3D Adjustment

The textile harness features unique 1-2-3-point depth settings. This offers the most precise fit attainable on a safety helmet.



Ventilation Options

Available with three ventilation options: non-vented, small vented, or large vented. Non-vented and small vent options provide electrical insulation up to 1000V, or choose large vents for optimal coolness and comfort.



Bespoke Your Mk®7.0

Strengthen corporate identity by applying a company logo to the Mk®7.0 safety helmet using the JSP Logo Express® service. Minimum order quantities and set-up charges apply.

LOGO









RANGE





JSP Limited. Worsham Mill. Minster Lovell. Oxford OX29 0TA. England.

Tel: +44 (0)1993 826050 / Fax: +44 (0)1993 824411 / Email: sales@jspsafety.com / Web: www.jspsafety.com

Do Not Publish without written permission from JSP Limited. Contact copyright@jspsafety.com. Information correct in the United Kingdom at date of issue and may be subject to change. Any third-party machine and automated translations processed by users may have inaccuracies and should not be relied upon.





DOWNLOADS



doc-helmets-mk-7.0.pdf (PDF)





JSP Limited. Worsham Mill. Minster Lovell. Oxford OX29 0TA. England.

 $Tel: + 44 \ (0) \\ 1993 \ 826050 \ / \ Fax: + 44 \ (0) \\ 1993 \ 824411 \ / \ Email: \\ sales@jspsafety.com \ / \ Web: \\ www.jspsafety.com \ / \ Web: \\ www.$





