

## 2m Adjustable Work Positioning Lanyard with Scaffold Hook

2m Adjustable Work Positioning Lanyard with Scaffold Hook / FAR0312



### DESCRIPTION

Adjustable restraint lanyard, adjustable up to 2m, made from 14mm polyamide 3-strand rope (complying with ISO 1140).

### OPTIONS

**2m Adjustable Work Positioning Lanyard with Scaffold Hook (FAR0312)**

### SAFETY STANDARDS

EN 358

## SPECIFICATIONS

Length  
2m Max.

Rope Ends  
Stitched and Covered With Polyethylene Protective Sleeve. Abrasion Resistant Thimbles Provided Within Loops

Adjustment Device  
Manual Ring Type Adjuster Of Forged Alloy Steel.

Material  
14mm Polyamide 3 Strand Twisted Rope  
(Complying to ISO 1140). Black and Red Tracer In the Rope To Indicate Degradation Of Material.

Protective Rope Sleeve  
No



Product Weight  
1070g

Delivered With  
1 Screwgate Connector of Alloy Steel. Gate  
Opening 18mm. Conforms to EN362 Class B & M. 1  
Alloy Steel Scaffold Hook. Gate Opening 15mm.  
Conforms to EN362 Class T

## DOWNLOADS

[Image Pack \(ZIP\)](#)

[doc-far0308-far0312.pdf \(PDF\)](#)



JSP Limited. Worsham Mill. Minster Lovell. Oxford OX29 0TA. England.

Tel: +44 (0)1993 826050 / Fax: +44 (0)1993 824411 / Email: [sales@jpsafety.com](mailto:sales@jpsafety.com) / Web: [www.jpsafety.com](http://www.jpsafety.com)

Do Not Publish without written permission from JSP Limited. Contact [copyright@jpsafety.com](mailto:copyright@jpsafety.com). Information correct in the United Kingdom at date of issue and may be subject to change. Any third-party machine and automated translations processed by users may have inaccuracies and should not be relied upon.

Page 2 of 2 / Issued 3 Feb 2026 / Copyright 2018 - 2026. JSP Limited. All Rights Reserved.

