FICHE TECHNIQUE

Longe de maintien en position de travail/retenue réglable Spartan™ 2m avec mousqueton grande ouverture

Longe de maintien en position de travail/retenue réglable Spartan™ 2m avec mousqueton grande ouverture / FAR0312



DESCRIPTION

Fabriquée en corde toronnée (3 torons) diamètre 14 mm (répondant à la norme ISO 1140).

OPTIONS

Longe de maintien en position de travail/retenue réglable Spartan™ 2m avec mousqueton grande ouverture (FAR0312)

NORMES

EN 358

JSP Limited. Worsham Mill. Minster Lovell. Oxford OX29 0TA. England.

Tel: +44 (0)1993 826050 / Fax: +44 (0)1993 824411 / Email: sales@jspsafety.com / Web: www.jspsafety.com

Do Not Publish without written permission from JSP Limited. Contact copyright@jspsafety.com. Information correct in the United Kingdom at date of issue and may be subject to change. Any third-party machine and automated translations processed by users may have inaccuracies and should not be relied upon.

INFORMATIONS TECHNIQUES

Longueur
2m Max.

Extrémités de corde
Chaque coté de la corde est cousu et recouvert d'une manche de protection en polyéthylène. Bague de protection anti-abrasion à l'intérieur des boucles.

Dispositif de réglage
Anneau en alliage acier pour un ajustement manuel et simple.

Livré avec
1 connecteur à vis en alliage acier. Ouverture 18mm. Conforme à la norme EN362 Classe B&M. 1 connecteur à grande ouverture en acier. Ouverture 15mm. Conforme à EN362 Classe T

Matériau
14mm Polyamide 3 Strand Twisted Rope (Complying to ISO 1140). Repère noir et rouge pour l'indication d'usure et la corde.

Manche de protection de la corde
Non

Poids du produit
1070g

TÉLÉCHARGEMENTS

Pack d'images (ZIP)
doc-far0308-far0312.pdf (PDF)

JSP Limited. Worsham Mill. Minster Lovell. Oxford OX29 0TA. England.

Tel: +44 (0)1993 826050 / Fax: +44 (0)1993 824411 / Email: sales@jspsafety.com / Web: www.jspsafety.com

Do Not Publish without written permission from JSP Limited. Contact copyright@jspsafety.com. Information correct in the United Kingdom at date of issue and may be subject to change. Any third-party machine and automated translations processed by users may have inaccuracies and should not be relied upon.