

ESPECIFICACIONES TÉCNICAS



Swiss One RIGI

1RIGBB21LB / 1RIGBB21LB



DESCRIPCIÓN

El best seller de la próxima década...

Sea cual sea su entorno de trabajo, RIGI ofrece la asociación perfecta de rendimiento, seguridad y estilo activo.

El exclusivo diseño de ajuste ceñido, el peso ultraligero... 19 gramos de comodidad y ajuste. Amplio campo de visión y un diseño que se adapta a todos los rostros... El ajuste ergonómico con patillas FlexoFit, planas y finas compatibles con cualquier protector auditivo o casco. Estas características permiten a los usuarios conseguir un ajuste cómodo y personalizado durante todo el día. Pruébalo... ¡adapta!

Disponible en una amplia gama de versiones de lentes... Antirrayas, revestimiento Excellence y una selección única de lentes Blue Blocker

OPCIONES

1RIG23CKN (1RIG23CKN)

1RIG23SKN (1RIG23SKN)

1RIGBB21AR (1RIGBB21AR)

1RIGBB21LB (1RIGBB21LB)

1RIGBB21LO (1RIGBB21LO)

1RIG21C (1RIG21C)

1RIG21S (1RIG21S)

NORMAS DE SEGURIDAD

EN 170 • EN 166



JSP Limited, Worsham Mill, Minster Lovell, Oxford OX29 0TA, England.

Tel: +44 (0)1993 826050 / Fax: +44 (0)1993 824411 / Email: sales@jspssafety.com / Web: www.jspssafety.com

Do Not Publish without written permission from JSP Limited. Contact copyright@jspssafety.com. Information correct in the United Kingdom at date of issue and may be subject to change. Any third-party machine and automated translations processed by users may have inaccuracies and should not be relied upon.

Page 1 of 2 / Issued 13 Feb 2025 / Copyright 2018 - 2025. JSP Limited. All Rights Reserved.



ESPECIFICACIONES



RADIATION PROTECTION BREAKDOWN filtering effect
Scale Number
2C



LIGHT TRANSMISSION BREAKDOWN Lens Shade number
1,4



Manufacturer's Trademark
Swiss One



Optical Class (1 – Class 1 – High quality for regular use. 2 – Class 2 – Medium quality for occasional use. 3 – Class 3 – Low quality for exceptional use)
1



Low Energy Impact resists a 6 mm, 0.86g ball @ 45 m/s °
Maximum protection for glasses
F



The letter T, immediately after the mechanical strength symbol, authorises use for high speed particles at extreme temperatures. (-5°C and +55°C) Optional
T

Blue Blocker Light Brown Lens
Sí

Anti-Scratch Coating (21 Code)
Sí

Soft End Tips - Flex Flat Temple Pressure Free
Sí

Lens Base Curve
9,5

Lightweight
Sí



Product Weight
19g

FLEXoFIT Technology
Sí

CARACTERÍSTICAS



Anti-niebla

Anti-niebla



Anti-arañazos

Anti-arañazos



Curva de la lente

Curva de la lente



Revestimiento de alto rendimiento

Revestimiento de alto rendimiento antiarañazos y antiniebla



Ligero

Ligero



Puntas blandas

Puntas blandas



Absorción UV 400

Absorción UV 400



Tecnología Flexofit

Tecnología flexofit

GAMA



DESCARGAR

[Colección de imágenes \(ZIP\)](#)

[doc-rigi.pdf \(PDF\)](#)



JSP Limited, Worsham Mill, Minster Lovell, Oxford OX29 0TA, England.

Tel: +44 (0)1993 826050 / Fax: +44 (0)1993 824411 / Email: sales@jsp-safety.com / Web: www.jsp-safety.com

Do Not Publish without written permission from JSP Limited. Contact copyright@jsp-safety.com. Information correct in the United Kingdom at date of issue and may be subject to change. Any third-party machine and automated translations processed by users may have inaccuracies and should not be relied upon.

Page 2 of 2 / Issued 13 Feb 2025 / Copyright 2018 - 2025. JSP Limited. All Rights Reserved.

