

TECHNICAL SPECIFICATION



EVOLite® Mid Peak Revolution® Flex Wheel Ratchet Vented Badge Holder lamp Bracket-CR2

White / AJB240-D00-100



DESCRIPTION

EVOLite® safety helmet with a clear plastic ID card holder that fits standard business card size identification. Simple push and slide mechanism. A lamp bracket can be positioned at the top of the unit.

OPTIONS

Green (AJB240-D00-300)
Grey (AJB240-D00-400)
Orange (AJB240-D00-800)
Red (AJB240-D00-600)
White (AJB240-D00-100)
Yellow (AJB240-D00-200)

SAFETY STANDARDS

EN 397



JSP Limited, Worsham Mill, Minster Lovell, Oxford OX29 0TA, England.






















Tel: +44 (0)1993 826050 / Fax: +44 (0)1993 824411 / Email: sales@jspsafety.com / Web: www.jspsafety.com

Do Not Publish without written permission from JSP Limited. Contact copyright@jspsafety.com. Information correct in the United Kingdom at date of issue and may be subject to change. Any third-party machine and automated translations processed by users may have inaccuracies and should not be relied upon.

Page 1 of 3 / Issued 13 Dec 2025 / Copyright 2018 - 2025, JSP Limited. All Rights Reserved.



SPECIFICATIONS

	Peak Mid		Impact Resistance 50 Joules
	Lateral Deformation Yes		Resistance to Molten Metals and Hot Solids (optional) Yes
	Maximum Temperature +50°C		Minimum Temperature -40°C
	ABS Shell Yes		Recyclable Shell
	Textile Harness		Depth Adjustment 3D Harness
	Wheel Ratchet Yes		Universal Accessories Slot Yes
	Ventilation Yes		Reflective Option Fitted
	Integrated Eyewear Optional		ID card holder Fitted
	BSI Kitemark Yes		Optional 4 point chinstrap (EN397 Compliant) Fitted
	JSPCheck Yes		Product Weight 350g
	Size 53-64cm		

FEATURES



Supreme Comfort

A 6-point textile cradle harness system & Chamlon™ cotton sweatband offer unrivalled comfort.



Firmest Fit Available

The deep nape strap enables the firmest retention of any helmet, keeping it firmly rooted on the head. Available with either the Revolution® Flex wheel ratchet or the OneTouch™ slip ratchet.



Accessories

A universal attachment slot enables firm fitting of a range of Surefit™ safety visors, and ear defenders. EVOSpec® Integrated eyewear is also available.



ID Card Holder

Clear plastic ID card holder that fits standard business card size identification. Simple push and slide mechanism. A lamp bracket can be positioned at the top of the unit.



3D Adjustment

The textile harness features unique 1-2-3 point depth settings. This offers the most precise fit attainable on an industrial safety helmet.



CR2™ Reflective

Using Class RA2, high intensity reflective. CR2 is the biggest step-up in night time visibility / reflectivity of head protection to date. Conforms to Class RA2, EN12899-1.



JSP Logo Express®

Strengthen your corporate identity by applying a company logo on a range of our safety helmets. Minimum order quantities and set-up charges apply.



Linesman Harness

4-point chinstrap harness for EVO® helmets. Ideal for working at height. Releases automatically with forces between 150 & 250 Newtons.



JSP Limited, Worsham Mill, Minster Lovell, Oxford OX29 0TA, England.

Tel: +44 (0)1993 826050 / Fax: +44 (0)1993 824411 / Email: sales@jspafety.com / Web: www.jspafety.com

Do Not Publish without written permission from JSP Limited. Contact copyright@jspafety.com. Information correct in the United Kingdom at date of issue and may be subject to change. Any third-party machine and automated translations processed by users may have inaccuracies and should not be relied upon.

Page 2 of 3 / Issued 13 Dec 2025 / Copyright 2018 - 2025, JSP Limited. All Rights Reserved.



- ☒ Back
- ☒ Sides



DOWNLOADS

-  [Image Pack \(ZIP\)](#)
-  [doc-invincible-evolute.pdf \(PDF\)](#)

