

# TECHNICAL SPECIFICATION



## 10m Wire Self-Retractable Lifeline

10m Wire Self-Retractable Lifeline / FAR0706



JSP Limited, Worsham Mill, Minster Lovell, Oxford OX29 0TA, England.

Tel: +44 (0)1993 826050 / Fax: +44 (0)1993 824411 / Email: [sales@jsp-safety.com](mailto:sales@jsp-safety.com) / Web: [www.jsp-safety.com](http://www.jsp-safety.com)

Do Not Publish without written permission from JSP Limited. Contact [copyright@jsp-safety.com](mailto:copyright@jsp-safety.com). Information correct in the United Kingdom at date of issue and may be subject to change. Any third-party machine and automated translations processed by users may have inaccuracies and should not be relied upon.

Page 1 of 4 / Issued 3 Apr 2026 / Copyright 2018 - 2026. JSP Limited. All Rights Reserved.





## DESCRIPTION

10m wire self-retractable lifeline in robust and durable plastic casing, equipped with steel swivel snap hook connector, and screw gate aluminium connector at anchorage point. This product also features a handle for convenient carrying.

## OPTIONS

**10m Wire Self-Retractable Lifeline (FAR0706)**

## SAFETY STANDARDS

EN 360



JSP Limited, Worsham Mill, Minster Lovell, Oxford OX29 0TA, England.

Tel: +44 (0)1993 826050 / Fax: +44 (0)1993 824411 / Email: sales@jgpsafety.com / Web: www.jgpsafety.com

Do Not Publish without written permission from JSP Limited. Contact copyright@jgpsafety.com. Information correct in the United Kingdom at date of issue and may be subject to change. Any third-party machine and automated translations processed by users may have inaccuracies and should not be relied upon.

Page 2 of 4 / Issued 3 Apr 2026 / Copyright 2018 - 2026. JSP Limited. All Rights Reserved.





JSP Limited. Worsham Mill. Minster Lovell. Oxford OX29 0TA. England.

Tel: +44 (0)1993 826050 / Fax: +44 (0)1993 824411 / Email: [sales@jspsafety.com](mailto:sales@jspsafety.com) / Web: [www.jspsafety.com](http://www.jspsafety.com)

Do Not Publish without written permission from JSP Limited. Contact [copyright@jspsafety.com](mailto:copyright@jspsafety.com). Information correct in the United Kingdom at date of issue and may be subject to change. Any third-party machine and automated translations processed by users may have inaccuracies and should not be relied upon.

Page 3 of 4 / Issued 3 Apr 2026 / Copyright 2018 - 2026. JSP Limited. All Rights Reserved.



## SPECIFICATIONS

Fall Indicator  
Yes

Material  
Galvanised Steel Wire 4.5mm Diameter

Sharp Edge  
No



Rated Weight / Load  
140kg

Delivered With  
1 Steel Swivel Snap Hook. Gate Opening 20mm.  
Conforms To EN362 Class T. 1 Screw Gate  
Aluminium Connector At The Anchorage Point.  
Gate Opening 22mm. Conforms To EN362 Class B.

Length  
10m

Shock Absorber  
Internal

Casing  
Robust and Durable Plastic



Product Weight  
3885g

## DOWNLOADS

 [Image Pack \(ZIP\)](#)

 [doc-far0705-far0706.pdf \(PDF\)](#)



JSP Limited, Worsham Mill, Minster Lovell, Oxford OX29 0TA, England.

Tel: +44 (0)1993 826050 / Fax: +44 (0)1993 824411 / Email: sales@jspsafety.com / Web: www.jspsafety.com

Do Not Publish without written permission from JSP Limited. Contact copyright@jspsafety.com. Information correct in the United Kingdom at date of issue and may be subject to change. Any third-party machine and automated translations processed by users may have inaccuracies and should not be relied upon.

Page 4 of 4 / Issued 3 Apr 2026 / Copyright 2018 - 2026. JSP Limited. All Rights Reserved.

