

10m Draad Zelfoprolbare Veiligheidslijn

10m Draad Zelfoprolbare Veiligheidslijn / FAR0706



JSP Limited, Worsham Mill, Minster Lovell, Oxford OX29 0TA, England.

Tel: +44 (0)1993 826050 / Fax: +44 (0)1993 824411 / Email: sales@jsp-safety.com / Web: www.jsp-safety.com

Do Not Publish without written permission from JSP Limited. Contact copyright@jsp-safety.com. Information correct in the United Kingdom at date of issue and may be subject to change. Any third-party machine and automated translations processed by users may have inaccuracies and should not be relied upon.

Page 1 of 4 / Issued 24 Apr 2025 / Copyright 2018 - 2025. JSP Limited. All Rights Reserved.





BESCHRIJVING

Zelfoprolbare reddingslijn van 10 m met draad in robuuste en duurzame kunststof behuizing, uitgerust met stalen draaibare karabijnhaakverbinding en aluminium schroefverbinding op het verankeringspunt. Dit product heeft ook een handvat om het

OPTIES

10m Draad Zelfoprolbare Veiligheidslijn (FAR0706)

VEILIGHEIDSNORMEN

EN 360



JSP Limited, Worsham Mill, Minster Lovell, Oxford OX29 0TA, England.

Tel: +44 (0)1993 826050 / Fax: +44 (0)1993 824411 / Email: sales@jspsafety.com / Web: www.jspsafety.com

Do Not Publish without written permission from JSP Limited. Contact copyright@jspsafety.com. Information correct in the United Kingdom at date of issue and may be subject to change. Any third-party machine and automated translations processed by users may have inaccuracies and should not be relied upon.

Page 2 of 4 / Issued 24 Apr 2025 / Copyright 2018 - 2025. JSP Limited. All Rights Reserved.



gemakkelijk te dragen.



JSP Limited. Worsham Mill. Minster Lovell. Oxford OX29 0TA. England.

Tel: +44 (0)1993 826050 / Fax: +44 (0)1993 824411 / Email: sales@jspsafety.com / Web: www.jspsafety.com

Do Not Publish without written permission from JSP Limited. Contact copyright@jspsafety.com. Information correct in the United Kingdom at date of issue and may be subject to change. Any third-party machine and automated translations processed by users may have inaccuracies and should not be relied upon.

Page 3 of 4 / Issued 24 Apr 2025 / Copyright 2018 - 2025. JSP Limited. All Rights Reserved.



SPECIFICATIES

Valindicator
Ja

Materiaal
Gegalvaniseerde staaldraad 4,5mm diameter

Scherpe rand
Nein



Nominaal gewicht / belasting
140 kg

Geleverd met
1 Stalen draaibare karabijnhaak. Poortopening 20 mm. Voldoet aan EN362 Klasse T. 1 Aluminium schroefverbinding bij het verankeringspunt. Poortopening 22 mm. Voldoet aan EN362 Klasse B.

Lengte
10m

Schokdemper
Intern

Behuizing
Robuust en duurzaam plastic



Gewicht product
3885g

DOWNLOADS

 [Pakket afbeeldingen \(ZIP\)](#)

 [doc-far0705-far0706.pdf \(PDF\)](#)



JSP Limited. Worsham Mill. Minster Lovell. Oxford OX29 0TA. England.

Tel: +44 (0)1993 826050 / Fax: +44 (0)1993 824411 / Email: sales@jssafety.com / Web: www.jssafety.com

Do Not Publish without written permission from JSP Limited. Contact copyright@jssafety.com. Information correct in the United Kingdom at date of issue and may be subject to change. Any third-party machine and automated translations processed by users may have inaccuracies and should not be relied upon.

Page 4 of 4 / Issued 24 Apr 2025 / Copyright 2018 - 2025. JSP Limited. All Rights Reserved.

