

# SPECYFIKACJA TECHNICZNA



## 10m urządzenie samohamowne

10m urządzenie samohamowne / FAR0706



JSP Limited, Worsham Mill, Minster Lovell, Oxford OX29 0TA, England.

Tel: +44 (0)1993 826050 / Fax: +44 (0)1993 824411 / Email: [sales@jsp-safety.com](mailto:sales@jsp-safety.com) / Web: [www.jsp-safety.com](http://www.jsp-safety.com)

Do Not Publish without written permission from JSP Limited. Contact [copyright@jsp-safety.com](mailto:copyright@jsp-safety.com). Information correct in the United Kingdom at date of issue and may be subject to change. Any third-party machine and automated translations processed by users may have inaccuracies and should not be relied upon.

Page 1 of 4 / Issued 19 Dec 2024 / Copyright 2018 - 2024. JSP Limited. All Rights Reserved.





## OPIS

10m urządzenie samohamowne, w wytrzymałej i trwałej obudowie z tworzywa sztucznego, wyposażony w stalowy, obrotowy zatrzaśnik i aluminiowy zatrzaśnik śrubowy w punkcie mocowania. Ten produkt posiada również uchwyt do wygodnego przenoszenia/przesuwania.

## OPCJE

**10m urządzenie samohamowne (FAR0706)**

## NORMY BEZPIECZEŃSTWA

EN 360



JSP Limited, Worsham Mill, Minster Lovell, Oxford OX29 0TA, England.

Tel: +44 (0)1993 826050 / Fax: +44 (0)1993 824411 / Email: sales@jssafety.com / Web: www.jssafety.com

Do Not Publish without written permission from JSP Limited. Contact copyright@jssafety.com. Information correct in the United Kingdom at date of issue and may be subject to change. Any third-party machine and automated translations processed by users may have inaccuracies and should not be relied upon.

Page 2 of 4 / Issued 19 Dec 2024 / Copyright 2018 - 2024, JSP Limited. All Rights Reserved.





JSP Limited. Worsham Mill. Minster Lovell. Oxford OX29 0TA. England.

Tel: +44 (0)1993 826050 / Fax: +44 (0)1993 824411 / Email: [sales@jspsafety.com](mailto:sales@jspsafety.com) / Web: [www.jspsafety.com](http://www.jspsafety.com)

Do Not Publish without written permission from JSP Limited. Contact [copyright@jspsafety.com](mailto:copyright@jspsafety.com). Information correct in the United Kingdom at date of issue and may be subject to change. Any third-party machine and automated translations processed by users may have inaccuracies and should not be relied upon.

Page 3 of 4 / Issued 19 Dec 2024 / Copyright 2018 - 2024. JSP Limited. All Rights Reserved.



## SPECYFIKACJE

Wskaźnik upadku

Tak

Długość

10m

Materiał

Drut stalowy ocynkowany o średnicy 4.5 mm

Amortyzator

Wewnętrzne

TESTOWANE KRAWĘDZIOWO

Nie

Obudowa

Solidne i trwałe tworzywo sztuczne

Szacowana waga / Obciążenie

140kg

Waga Produktu

3885g

Dostarczane z

1 Stalowy obrotowy karabińczyk Otwarcie 20mm

Zgodny z normą EN362 klasa T. Śrubowy karabinek

aluminiowy w miejscu zakotwienia. Otwarcie 22mm

Jest zgodny z EN362 Klasa B.

## ZASTOSOWANIE

Tylko ogólne wytyczne i nie powinny być uważane za substytut pełnej oceny ryzyka

Aeronautyka

## PLIKI DO POBRANIA

 [Zbiór zdjęć \(ZIP\)](#)

 [doc-far0705-far0706.pdf \(PDF\)](#)



JSP Limited. Worsham Mill. Minster Lovell. Oxford OX29 0TA. England.

Tel: +44 (0)1993 826050 / Fax: +44 (0)1993 824411 / Email: sales@jspsafety.com / Web: www.jspsafety.com

Do Not Publish without written permission from JSP Limited. Contact copyright@jspsafety.com. Information correct in the United Kingdom at date of issue and may be subject to change. Any third-party machine and automated translations processed by users may have inaccuracies and should not be relied upon.

Page 4 of 4 / Issued 19 Dec 2024 / Copyright 2018 - 2024. JSP Limited. All Rights Reserved.

