


TECHNICAL SPECIFICATION



Swiss One ARVEL

1ARVG21IO / 1ARVG21IO



DESCRIPTION

Comfort and design without compromise. Soft material components utilised around the sensitive parts of the face, Arvel™ is lightweight, with a smart finish, one of the best designs defining our Swiss One signature... Try it, adopt it and enjoy stylish safety!

OPTIONS

1ARVG21IO (1ARVG21IO)

1ARVS23S (1ARVS23S)

SAFETY STANDARDS

EN 172 • EN 166



JSP Limited. Worsham Mill. Minster Lovell. Oxford OX29 0TA. England.

Tel: +44 (0)1993 826050 / Fax: +44 (0)1993 824411 / Email: sales@jsp-safety.com / Web: www.jsp-safety.com

Do Not Publish without written permission from JSP Limited. Contact copyright@jsp-safety.com. Information correct in the United Kingdom at date of issue and may be subject to change. Any third-party machine and automated translations processed by users may have inaccuracies and should not be relied upon.

Page 1 of 2 / Issued 13 Dec 2025 / Copyright 2018 - 2025. JSP Limited. All Rights Reserved.



SPECIFICATIONS



RADIATION PROTECTION BREAKDOWN filtering effect
Scale Number
5



Manufacture's Trademark Swiss One
Swiss One



Low Energy Impact resists a 6 mm, 0.86g ball @ 45 m/s °
Maximum protection for glasses
F

Anti-Scratch Coating (21 Code)
Yes

Lightweight
Yes

Soft Nose Pad
Yes



LIGHT TRANSMISSION BREAKDOWN Lens Shade number
1.7



Optical Class (1 – Class 1 – High quality for regular use. 2 – Class 2 – Medium quality for occasional use. 3 – Class 3 – Low quality for exceptional use)
1



The letter T, immediately after the mechanical strength symbol, authorises use for high speed particles at extreme temperatures. (-5°C and +55°C) Optional
T

Lens Base Curve
9

Soft End Tips - Flex Flat Temple Pressure Free
Yes



Product Weight
25g

FEATURES



Anti-mist

Anti-mist



Soft End Tips

Soft end tips



Lightweight

Lightweight



Lens Curve

Lens curve



Anti-scratch

Anti-scratch



Soft Nose Pad

Soft nose pad



UV 400 absorption

UV 400 absorption



High Performance Coating

Anti-scratch / anti-fog high performance coating

RANGE



DOWNLOADS



[Image Pack \(ZIP\)](#)



[doc-arvel.pdf \(PDF\)](#)



JSP Limited, Worsham Mill, Minster Lovell, Oxford OX29 0TA, England.

Tel: +44 (0)1993 826050 / Fax: +44 (0)1993 824411 / Email: sales@jsp-safety.com / Web: www.jsp-safety.com

Do Not Publish without written permission from JSP Limited. Contact copyright@jsp-safety.com. Information correct in the United Kingdom at date of issue and may be subject to change. Any third-party machine and automated translations processed by users may have inaccuracies and should not be relied upon.

Page 2 of 2 / Issued 13 Dec 2025 / Copyright 2018 - 2025, JSP Limited. All Rights Reserved.

