TECHNICAL SPECIFICATION

EVOGuard®M Forestry Helmet Systems

EVOGuard®M3 Forestry Helmet System / AKE24A-500-800



DESCRIPTION

The EVOGuard®M Forestry browguard and helmet systems are innovative solutions to protect the wearer in a multitude of high risk working environments. All EVOGuard® visor components are fully compatible with a range of existing EVO® helmet models.

OPTIONS

EVOGuard®M3 Forestry Helmet System (AKE24A-500-800)

EVOGuard®M3 Forestry Helmet System - with Throat Cover & Sun Cape (AKE24E-200-800)

EVOGuard®M2 Forestry Helmet System (AKE24A-400-800)

SAFETY STANDARDS

EN 397 • EN 352-3 • EN 1731 • EN 166

JSP Limited. Worsham Mill. Minster Lovell. Oxford OX29 0TA. England.

Tel: +44 (0)1993 826050 / Fax: +44 (0)1993 824411 / Email: sales@jspsafety.com / Web: www.jspsafety.com

Do Not Publish without written permission from JSP Limited. Contact copyright@jspsafety.com. Information correct in the United Kingdom at date of issue and may be subject to change. Any third-party machine and automated translations processed by users may have inaccuracies and should not be relied upon.

SPECIFICATIONS

Peak
Standard

Lateral Deformation
Yes

Maximum Temperature
+50°C

ABS Shell
Yes

Depth Adjustment
3D Harness

Ventilation
No

Integrated Eyewear
Fitted

Optional 2 point chinstrap (EN397 & EN 812 compliant)
Optional

Mounting
Helmet

Cup Material
ABS

Hygiene
Hygiene Kit

Low Energy Impact resists a 6 mm, 0.86g ball @ 45 m/s ˚
Maximum protection for glasses
F

Visor Length
18cm

BSI Kitemark
Yes

JSPCheck
Yes

Impact Resistance
50 Joules

Molten Metal
Yes

Minimum Temperature
-40°C

Textile
Harness

Wheel Ratchet
Yes

Reflective Option
Fitted

ID card holder
Optional

Optional 4 point chinstrap (EN397 Compliant)
Fitted

SNR
31 dB

Adjustable
Yes

Manufacturer's Trademark
JSP Dagger


Visible Light Transmittance (VLT)
80%

Material
ABS Frame and Woven Stainless Steel Mesh Visor

Recyclable
Yes

Product Weight
809g

FEATURES



Visor Range

Two high performance complete forestry systems are available, enabling users to select the perfect visor for their task and price point.



Dual Layer Protection

The EVOGuard®M Forestry Helmet and Forestry Browguard Systems both feature a secondary layer of eye protection in the form of the integrated EVOSpec® polycarbonate retractable eyeshield.



Balanced & Secure

Fitted to a browguard or helmet, the self-lubricating nylon hinges hold the visor securely in position even during extreme movement, whilst offering balanced, even weight distribution.



Product Compatibility

Designed to maximise compatibility with a broad range of JSP products, such as the Force®8 respirator with PressToCheck™, Springfit™ disposable masks and the Sonis® helmet mounted ear defender range.

JSP Limited. Worsham Mill. Minster Lovell. Oxford OX29 0TA. England.

Tel: +44 (0)1993 826050 / Fax: +44 (0)1993 824411 / Email: sales@jspsafety.com / Web: www.jspsafety.com

Do Not Publish without written permission from JSP Limited. Contact copyright@jspsafety.com. Information correct in the United Kingdom at date of issue and may be subject to change. Any third-party machine and automated translations processed by users may have inaccuracies and should not be relied upon.



Supreme Comfort

Features an easy to use Revolution® wheel ratchet and a 3D-Adjustment harness, which offers 1-2-3 point depth settings for increased adaptability to ensure a perfect, secure fit.



Coverage

EVOGuard® visors provide comprehensive facial coverage without limiting movement or vision.

LOGO

- [x] Front

RANGE

EVOGUARD M
FORESTRY RANGE

DOWNLOADS

Image Pack (ZIP)
doc-evoguard.pdf (PDF)

JSP Limited. Worsham Mill. Minster Lovell. Oxford OX29 0TA. England.

Tel: +44 (0)1993 826050 / Fax: +44 (0)1993 824411 / Email: sales@jspsafety.com / Web: www.jspsafety.com

Do Not Publish without written permission from JSP Limited. Contact copyright@jspsafety.com. Information correct in the United Kingdom at date of issue and may be subject to change. Any third-party machine and automated translations processed by users may have inaccuracies and should not be relied upon.