

TECHNICAL SPECIFICATION



Spartan™ 2m Twin Fall Arrest Lanyard

Spartan™ 2m Twin Fall Arrest Lanyard / FAR0307



DESCRIPTION

Spartan™ fall arrest lanyards are manufactured in 33mm flat webbing with steel connectors. Complete with karabiner and 2 scaffold hooks.

OPTIONS

Spartan™ 2m Twin Fall Arrest Lanyard (FAR0307)

SAFETY STANDARDS

EN 355



JSP Limited. Worsham Mill. Minster Lovell. Oxford OX29 0TA. England.

Tel: +44 (0)1993 826050 / Fax: +44 (0)1993 824411 / Email: sales@jpsafety.com / Web: www.jpsafety.com

Do Not Publish without written permission from JSP Limited. Contact copyright@jpsafety.com. Information correct in the United Kingdom at date of issue and may be subject to change. Any third-party machine and automated translations processed by users may have inaccuracies and should not be relied upon.

Page 1 of 2 / Issued 3 Feb 2026 / Copyright 2018 - 2026. JSP Limited. All Rights Reserved.



SPECIFICATIONS

Fall Indicator	Length
Yes	2m
Material	Shock Absorber
30mm Polyester Webbing With Textile Loops On Both Ends	External
Sharp Edge	Rope Ends
No	X
Protective Rope Sleeve	Product Weight
No	1700g

Delivered With
1 Screw Gate Connector In Alloy Steel. Gate Opening 18mm. Conforms to EN362 Class B & M. 2 Alloy Steel Scaffold Hooks. Gate Opening 50mm. Conforms to EN362 Class T.



DOWNLOADS

-  [Image Pack \(ZIP\)](#)
-  [doc-far0307-far0318.pdf \(PDF\)](#)

JSP Limited. Worsham Mill. Minster Lovell. Oxford OX29 0TA. England.

Tel: +44 (0)1993 826050 / Fax: +44 (0)1993 824411 / Email: sales@jpsafety.com / Web: www.jpsafety.com

Do Not Publish without written permission from JSP Limited. Contact copyright@jpsafety.com. Information correct in the United Kingdom at date of issue and may be subject to change. Any third-party machine and automated translations processed by users may have inaccuracies and should not be relied upon.



Page 2 of 2 / Issued 3 Feb 2026 / Copyright 2018 - 2026. JSP Limited. All Rights Reserved.

