TECHNICAL SPECIFICATION

Spartan™ 2m Twin Fall Arrest Lanyard

Spartan™ 2m Twin Fall Arrest Lanyard / FAR0307



DESCRIPTION

Spartan™ fall arrest lanyards are manufactured in 33mm flat webbing with steel connectors. Complete with karabiner and 2 scaffold hooks.

OPTIONS

Spartan™ 2m Twin Fall Arrest Lanyard (FAR0307)

SAFETY STANDARDS

EN 355

JSP Limited. Worsham Mill. Minster Lovell. Oxford OX29 0TA. England.

Tel: +44 (0)1993 826050 / Fax: +44 (0)1993 824411 / Email: sales@jspsafety.com / Web: www.jspsafety.com

Do Not Publish without written permission from JSP Limited. Contact copyright@jspsafety.com. Information correct in the United Kingdom at date of issue and may be subject to change. Any third-party machine and automated translations processed by users may have inaccuracies and should not be relied upon.

SPECIFICATIONS

Fall Indicator
Yes

Length
2m

Material
30mm Polyester Webbing With Textile Loops On Both Ends

Shock Absorber
External

Sharp Edge
No

Rope Ends
X

Protective Rope Sleeve
No

Product Weight
1700g

Delivered With
1 Screw Gate Connector In Alloy Steel. Gate Opening 18mm. Conforms to EN362 Class B & M. 2 Alloy Steel Scaffold Hooks. Gate Opening 50mm. Conforms to EN362 Class T.

DOWNLOADS

Image Pack (ZIP)
doc-far0307-far0318.pdf (PDF)

Do Not Publish without written permission from JSP Limited. Contact copyright@jspsafety.com. Information correct in the United Kingdom at date of issue and may be subject to change. Any third-party machine and automated translations processed by users may have inaccuracies and should not be relied upon.