# TECHNICAL SPECIFICATION



## Spartan™ 2m Twin Fall Arrest Lanyard

Spartan™ 2m Twin Fall Arrest Lanyard / FAR0307



### DESCRIPTION

Spartan<sup>™</sup> fall arrest lanyards are manufactured in 33mm flat webbing with steel connectors. Complete with karabiner and 2 scaffold hooks.

#### OPTIONS

Spartan™ 2m Twin Fall Arrest Lanyard (FAR0307)

SAFETY STANDARDS

EN 355















#### **SPECIFICATIONS**

Fall Indicator

Yes

Material

30mm Polyester Webbing With Textile Loops On

Both Ends

Sharp Edge

No

Protective Rope Sleeve

No

**Delivered With** 

1 Screw Gate Connector In Alloy Steel. Gate Opening 18mm. Conforms to EN362 Class B & M. 2 Alloy Steel Scaffold Hooks. Gate Opening 50mm. Conforms to EN362 Class T.

Length 2m

Shock Absorber

External

Rope Ends

Χ



**Product Weight** 

1700g

#### DOWNLOADS











JSP Limited. Worsham Mill. Minster Lovell. Oxford OX29 0TA. England.

Tel: +44 (0)1993 826050 / Fax: +44 (0)1993 824411 / Email: sales@jspsafety.com / Web: www.jspsafety.com





